

HI-SHEEN GAS & OIL RESISTANT SEALER

September, 09 Page 1 of 2

PRODUCT

TARGET® Hi-Sheen Gas & Oil Resistant Sealer is a clear, solvent borne, acrylic coating designed to protect concrete and exposed aggregate flooring and walkways. TARGET Hi-Sheen Gas & Oil Resistant Sealer resists alkaline cleaners, salts, grease, gasoline and most aliphatic solvents.

USES

TARGET Hi-Sheen Gas & Oil Resistant Sealer is used as a gloss dustproof, water repellent and sealer for vertical and horizontal concrete surfaces. TARGET Hi-Sheen Gas & Oil Resistant Sealer dries to a durable, glossy surface that is highly abrasion resistant and allows for easy cleaning of dust, dirt, oil and grease.

GLOSS

High - a two coat application will produce a glossy surface on smooth concrete.

COLORS

The standard product is a colorless, transparent liquid. Colored material is available to match TARGET Colored Floor Hardeners.

COVERAGE

On uncoated concrete: 6.1 - 8.6 m²/liter (250 - 350 ft²/US gallon)
Recoat: 7.4 - 12.3 m²/litre (300 - 500 ft²/US gallon)

NOTE: Coverage rates are approximate and vary with surface porosity.

DRYING TIMES

30 to 40 minutes to touch
1 to 3 hours hard
4 hours re-coat

CLEAN-UP

Xylene, toluene or aromatic solvent.

T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D

Product performance is affected by many factors, including storage, method and conditions of application and use. User testing is ESSENTIAL to determine suitability of product for intended method of application and use. Target's SOLE WARRANTY is that the product has been manufactured to specifications. No oral or written information or advice shall increase this warranty or create new warranties. Target's SOLE LIABILITY is to replace product proved defective. In no event shall Target be liable for any consequential, indirect or other damages whether arising from negligence or otherwise.

TARGET is a registered trade-mark of Quikrete Canada Holdings Limited. Target Products Ltd. is an authorized licensee.



HI-SHEEN GAS & OIL RESISTANT SEALER

September, 09 Page 2 of 2

PROCEDURES

Surface must be dry and clean of oils, dirt or other contaminants. Temperature should be above 5° C (41° F). New or old concrete surfaces that have not been coated before should be cleaned to remove alkaline materials and open up the surface for better penetration. Allow 3 to 5 days for the water to dry out before application of the sealer. For best results use a roller or low pressure spray equipment and apply in a continuous film. DO NOT apply in direct sunlight. For increased penetration into the concrete, reduce the TARGET Hi-Sheen Gas & Oil Resistant Sealer with 10-15% Aromatic Solvent for the first coat then apply a full coat (without thinning) to ensure long-lasting protection. DO NOT apply over curing compounds or any other coatings or sealers.

CAUTION

- This product is not resistant to hydraulic fluids, alcohols, and certain solvent cleaners. Contact your TARGET representative for advice if there is any doubt concerning the application of the product.
- TARGET Hi-Sheen Gas & Oil Resistant Colored Sealer is NOT a paint, it is NOT designed to have hiding capabilities. DO NOT use colored sealers except in conjunction with appropriately colored concrete. Always do a test patch to test for coverage rate.
- This product is flammable in its liquid form. Use only in well ventilated areas and away from open flames, pilot lights, sparks or heat. Avoid breathing of vapor. Harmful if swallowed.
- Adequate ventilation is critical during application and drying of TARGET Hi-Sheen Gas & Oil Resistant Sealer. Fumes given off during this period are flammable.

Product performance is affected by many factors, including storage, method and conditions of application and use. User testing is ESSENTIAL to determine suitability of product for intended method of application and use. Target's SOLE WARRANTY is that the product has been manufactured to specifications. No oral or written information or advice shall increase this warranty or create new warranties. Target's SOLE LIABILITY is to replace product proved defective. In no event shall Target be liable for any consequential, indirect or other damages whether arising from negligence or otherwise.

TARGET is a registered trade-mark of Quikrete Canada Holdings Limited. Target Products Ltd. is an authorized licensee.



T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D