

HYDRATED LIME TYPE S

September, 09 Page 1 of 1

PRODUCT AND USES

A white powder designed as an additive for use with Sand and Portland Cement in masonry mortar, exterior plaster and stucco. May also be used for agricultural purposes.

ADVANTAGES

- Good water retention
- Easy to spread
- Eliminated bleeding in mortar
- Creates a buttery effect in Stucco
- Good bond strength to help prevent cracks and water leaks

MIX RATIOS

MORTAR, TYPE N

1 part Portland Cement - 1 part Type S Lime - 4 ½ - 7 parts Sand

PLASTER

SCRATCH COAT

1 part Portland Cement - 1 part Type S Lime - 8 parts Sand

BROWN COAT

1 part Portland Cement - 1 part Type S Lime - 8 parts Sand

FINISH COAT

1 part Portland Cement - 1 part Type S Lime - 8 parts Sand

PACKAGING

22 kg (50 lb) bag

CAUTION

- Hydrated lime can burn the eyes resulting in severe eye injury. Wear dust proof goggles or other appropriate eye protection while using this product.
- Hydrated lime can irritate the skin. Protect exposed skin with gloves, long sleeved clothing and other covering to avoid contact. In addition apply protective cream to the face, hand, neck, waist and ankles.
- Hydrated lime can irritate and injure internal tissues if inhaled or ingested. Wear an approved respirator while using this product.

Manufactured by Chemical Lime

Product performance is affected by many factors, including storage, method and conditions of application and use. User testing is ESSENTIAL to determine suitability of product for intended method of application and use. Target's SOLE WARRANTY is that the product has been manufactured to specifications. No oral or written information or advice shall increase this warranty or create new warranties. Target's SOLE LIABILITY is to replace product proved defective. In no event shall Target be liable for any consequential, indirect or other damages whether arising from negligence or otherwise.



T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D