

TARGET PRIMER

October, 04 Page 1 of 2

PRODUCT

TARGET® Primer is an aqueous emulsion of a polymer and chemical admixtures. It is designed for use as a floor sealer and primer in conjunction TARGET Vetonit Plaano SL Plus, TARGET Tech Top Premium, TARGET Tech Top Standard and TARGET Floor Leveller C26 UL.

APPEARANCE

White, milky liquid

USES

TARGET Primer is intended only for use as a sealer and primer for surfaces to which TARGET Vetonit Plaano SL Plus, TARGET Tech Top Premium, TARGET Tech Top Standard or TARGET Floor Leveller C26 UL are to be applied.

PROCEDURES

1. Prepare existing concrete or sub-floor surfaces by removing all traces of dirt, dust, oil, grease, efflorescence, laitance and loose or deteriorated material. Sweep, vacuum clean, or use air jets to remove all loose material. In most cases mechanical roughening of concrete by shotblasting, sandblasting or high pressure water blasting is desirable. Do not acid etch.
2. The primer is mixed with clean water before application at a ratio of 1 part of TARGET Primer to 3 parts water by volume.
3. Apply the primer mixture to the floor by brush or roller (do not spray) before placing TARGET Vetonit Plaano SL Plus, TARGET Tech Top Premium, TARGET Tech Top Standard or TARGET Floor Leveller C26 UL. Additional brushing or rolling of the applied primer is required to ensure adequate sealing if any dust is present on the floor. Allow the primer to become surface-dry before applying the levelling material. A drying time of not less than two hours is usually required. On porous or highly absorbent surfaces, two coats of primer mixture should be applied to ensure sealing of voids. Allow a drying time of 1 to 2 hours between coats.
4. Formation of pools of primer should be avoided if possible. Any pools should be removed by spreading out with a brush prior to setting.

TEMPERATURE

The concrete or sub-floor and air temperatures should be kept above 5°C (41°F) during application of TARGET Primer.

CAUTION

- DO NOT allow TARGET Primer to freeze.
- DO NOT place TARGET Vetonit Plaano SL Plus, TARGET Tech Top Premium, TARGET Tech Top Standard or TARGET Floor Leveller C26 UL over pools of TARGET Primer. The primer should be applied uniformly to achieve the required degree of penetration and sealing.

Product performance is affected by many factors, including storage, method and conditions of application and use. User testing is ESSENTIAL to determine suitability of product for intended method of application and use. Target's SOLE WARRANTY is that the product has been manufactured to specifications. No oral or written information or advice shall increase this warranty or create new warranties. Target's SOLE LIABILITY is to replace product proved defective. In no event shall Target be liable for any consequential, indirect or other damages whether arising from negligence or otherwise.

TARGET is a registered trade-mark of Tegrat Holdings Ltd. Target Products Ltd. is an authorized licensee.



T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D

TARGET PRIMER

October, 04 Page 2 of 2

COVERAGE

At the specified dilution ratio, the approximate coverage obtained from concentrated TARGET Primer is 14 m² per liter (570 ft² per US gallon) per coat for most surfaces.

T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D

Product performance is affected by many factors, including storage, method and conditions of application and use. User testing is ESSENTIAL to determine suitability of product for intended method of application and use. Target's SOLE WARRANTY is that the product has been manufactured to specifications. No oral or written information or advice shall increase this warranty or create new warranties. Target's SOLE LIABILITY is to replace product proved defective. In no event shall Target be liable for any consequential, indirect or other damages whether arising from negligence or otherwise.

TARGET is a registered trade-mark of Tegrat Holdings Ltd. Target Products Ltd. is an authorized licensee.

