

BLACK WALNUT SHELL GRIT & ENGLISH WALNUT SHELL GRIT

May, 05 Page 1 of 2

PRODUCT

TARGET® Walnut Shell can be used to remove suspended solids and organic material from produced water, surface water and river, lake and well water. Walnut Shell Grit treats and removes suspended solids, oily residues, ash and metallic hydroxides from industrial liquids in power generation, metal working, and municipal chemical petroleum and petrochemical applications.

OTHER USES

TARGET Walnut Shell Grit prevents lost circulation on oil well drilling. Provides a non-skid enhancer in abrasive paints around swimming pools, walkways, dock boards and other areas where a rough surface is required. Serves as a filler prior to burnout – a porosity enhancer for grinding wheels and ceramics. Preserves gel-coat when removing paint from fiberglass boats. Wide range of surface patterns can be achieved with 7 grades of Walnut Shell Grit (6/12 to 60/100) available.

PHYSICAL PROPERTIES

Non-toxic, **filter media**, blast-cleaning media.

Specific gravity: 1.2 – 1.4

Angular; multi-faceted

20-40 Fine English Walnut Shell Grit

	TYPICAL	MAXIMUM
MOISTURE (by weight)	7%-8%	11%
TOLUENE SOLUBILITY (by weight)	0.6%-0.8%	1.5%

PARTICLE SIZE DISTRIBUTION(cumulative percent retained on screen)

U.S. STANDARD SIEVE#	TOLERANCE	TYPICAL WALNUT SHELL PRODUCED FOR TARGET
#12	0.1%	NIL
#18	10% max	5 – 7%
#40	88% min	92 - 94%
#100	2% min	99.8%

Product performance is affected by many factors, including storage, method and conditions of application and use. User testing is ESSENTIAL to determine suitability of product for intended method of application and use. Target's SOLE WARRANTY is that the product has been manufactured to specifications. No oral or written information or advice shall increase this warranty or create new warranties. Target's SOLE LIABILITY is to replace product proved defective. In no event shall Target be liable for any consequential, indirect or other damages whether arising from negligence or otherwise.

TARGET is a registered trade-mark of Tegrat Holdings Ltd. Target Products Ltd. is an authorized licensee.

T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D



BLACK WALNUT SHELL GRIT & ENGLISH WALNUT SHELL GRIT

T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D

PHYSICAL PROPERTIES con't

12-20 Medium English Walnut Shell Grit

	TYPICAL	MAXIMUM
MOISTURE (by weight)	7%-8%	11%
TOLUENE SOLUBILITY (by weight)	0.6%-0.8%	1.5%

PARTICLE SIZE DISTRIBUTION (percent on screen)

U.S. STANDARD SIEVE#	TOLERANCE	TYPICAL WALNUT SHELL PRODUCED FOR TARGET
+4	NIL	NIL
+10	0.0%-10.0%	0.5%
+20	85.0%-100.0%	96.5%
+30	0.0%-10.0%	3.0%
-30	5.0 (max) %	1.0%

CAUTION

Although Walnut Shell Grit can be used for blasting of concrete or wood surfaces, a test section should be done before proceeding with a project to ensure that the particles of abrasive do not become embedded in the work.

PACKAGING

All grades of Walnut Shell Grit are available in 22.68kg (50 lb) paper bags and 907.20kg (2000 lb) or 1134kg (2500 lb) super sacks. Product available in the following sizes:

6/12	18/40
8/12	40/60
12/20	60/100
20/40	

All oil well grades and custom grades available.

SAFETY

TARGET Walnut Shell Grit abrasive does not contain any hazardous ingredients. All appropriate safety precautions must be followed when using Walnut Shell Grit or any other material for abrasive applications. Consult your local Industrial Health & Safety Regulation, NIOSH or other requirements for guidance on the required safety procedures and equipment.

Product performance is affected by many factors, including storage, method and conditions of application and use. User testing is ESSENTIAL to determine suitability of product for intended method of application and use. Target's SOLE WARRANTY is that the product has been manufactured to specifications. No oral or written information or advice shall increase this warranty or create new warranties. Target's SOLE LIABILITY is to replace product proved defective. In no event shall Target be liable for any consequential, indirect or other damages whether arising from negligence or otherwise.

