



PRODUCT GUIDE

CEMENT & CONCRETE PRODUCTS



HIGH-STRENGTH CONCRETE MIXES



FAST-SET CONCRETE MIX



CONCRETE RESURFACING



CONCRETE REPAIR



MORTAR MIXES



SELF-LEVELING UNDERLAYMENTS



Your partner in quality • For all your concrete needs

Fast Setting Concrete No Mixing Required



TABLE OF CONTENTS

ITEM #	PRODUCT	PAGE
CONCRETE PRODUCTS		
110125	CONCRETE MIX • 25 kg bag	1
100465	POSTHASTE® CONCRETE MIX • 25 kg bag.....	1
100425	QUIKRETE® FAST SETTING CONCRETE • 25 kg bag	2
100725	QUIKRETE® 6000 • 25 kg bag.....	2
110682	COUNTERTOP MIX • 36.3 kg bag	3
110326	SAND / TOPPING MIX • 25 kg bag	3
158556	PORTLAND EXPANDING GROUT • 22.7 kg bag	4
124152	COMMERCIAL GRADE FASTSET™ Mortar Repair - 22 kg.....	4
158553	COMMERCIAL GRADE FASTSET™ All-Crete™ - 22 kg	5
MASONRY PRODUCTS		
113655	MASON MIX (TYPE S MORTAR) • 25 kg bag.....	5
115525	WATER RESISTANT PARGING MIX • 25 kg bag.....	6
123151	QUIKWALL SURFACE BONDING CEMENT – GRAY • 22.7 kg bag.....	6
CEMENTS AND LIME		
112425, 405942	GU (TYPE 10) CEMENT • 40 kg bag, 20 kg bag.....	7
112532	MCS (MORTAR S) CEMENT • 30 kg bag.....	7
112479	HE (TYPE 30) PORTLAND CEMENT • 40 kg bag	8
9994022	HS (TYPE 50) PORTLAND CEMENT • 20 kg bag, 40 kg bag	8
9994010	WHITE PORTLAND CEMENT FEDERAL WHITE • 42 kg bag	8
405951	PORTLAND CEMENT LIME BLEND • 30 kg bag.....	9
9994028	HYDRATED LIME – TYPE 'S' • 23 kg bag.....	9
9994035	HYDRATED LIME – TYPE 'N' • 22.68 kg bag	9
REPAIR PRODUCTS - BAGS		
113318	BONDED TOPPING MIX • 18 kg bag.....	10
113147	ReCap™ RESURFACER • 18 kg bag.....	10
124958	FAST-SET SELF-LEVELING FLOOR RESURFACER • 22 kg	11
170125	BLACK TOP PATCH • 25 kg bag	11
HARDSCAPES - SANDS AND AGGREGATE PRODUCTS		
111325	PREMIUM PLAY SAND • 25 kg bag.....	12
115125	ALL PURPOSE GRAVEL • 25 kg bag.....	12
115155	BASE ROCK • 25 kg bag.....	13
115036	PATIO PAVER JOINTING SAND • 36 kg bag	13
115831	TRACTION SAND • 18 kg bag	13
99933050	SILICA ABRASIVE 30-50 • 22.7 kg bag.....	14
116036	1/4 DOWN – LIMESTONE • 25 kg bag.....	14

TABLE OF CONTENTS

ITEM #	PRODUCT	PAGE
HARDSCAPES - EARTH ESSENTIALS		
137550	PLAY SAND EARTH ESSENTIALS • 18 kg bag.....	15
127558	POLYMERIC JOINTING SAND EARTH ESSENTIALS • 18 kg bag.....	15
137546	LIMESTONE SCREENINGS EARTH ESSENTIALS • 18 kg bag.....	15
137530	RED CRUSHED TILE EARTH ESSENTIALS • 18 kg bag	15
137504	WHITE ROCK EARTH ESSENTIALS • 18 kg bag	15
137517	BEACH PEBBLES EARTH ESSENTIALS • 18 kg bag.....	15
137510	PEA GRAVEL EARTH ESSENTIALS • 18 kg bag	15
137520	DRAINAGE GRAVEL EARTH ESSENTIALS • 18 kg bag	15
MISCELLANEOUS PRODUCTS		
692316, 692251, 2, 3	QUIK-TUBE® BUILDING FORMS • 6" x 8', 8" x 8', 10" x 8', 12" x 8' EA.....	15
692132	WALK MAKER® BUILDING FORM • 2' x 2' X 2" EA.....	15
131720,1,2,3	LIQUID CEMENT COLOUR • 296 ml bottle	16
691741	BACKER ROD • 3/4" dia x 20' EA.....	16
691706	EXPANSION JOINT STRIPS • 5'-0" long EA.....	17
861016	ACRYLIC FORTIFIER • 0.95 L bottle	17
860112	CONCRETE & ASPHALT CLEANER - CONCENTRATE • 946 ml bottle	18
873102	ACRYLIC CONCRETE CURE & SEAL (SATIN) • 3.8 L.....	18
REPAIR PRODUCTS – PATCHING PRODUCTS		
113304	BONDED TOPPING MIX • 4.5 kg pail	19
112612, 112606	HYDRAULIC WATER STOP CEMENT • 4.5 kg, 9 kg.....	19
124512	ANCHORING CEMENT • 4.5 kg pail.....	20
124012	QUICK-SETTING CEMENT • 4.5 kg pail.....	20
990203, 990216	CONCRETE BONDING ADHESIVE • 3.8 L, 0.95 L bottle	21
865036	CONCRETE PATCHING COMPOUND • 946 ml pail.....	21
124116	ZIP AND MIX REPAIR MORTAR • 1.35 kg bag	22
865033	PRE-MIXED STUCCO PATCH • 0.95 L pail	22
120145	EXTERIOR STUCCO PATCH • 4.5 kg pail.....	22
REPAIR PRODUCTS – JOINT AND CRACK REPAIR		
864002	GREY CONCRETE CRACK SEALER • 946 ml bottle.....	23
862012	CONCRETE REPAIR • 296 ml tube	23
865011	STUCCO CRACK REPAIR • 296 ml tube.....	24
862002	MORTAR REPAIR • 296 ml tube	24
862025	FIREPLACE MORTAR • 296 ml tube	25
862019	POLYURETHANE MORTAR JOINT SEALANT • 296 ml tube.....	25
866012, 866032	POLYURETHANE SEALANT GRAY – SELF LEVELLING • 300 ml, 858 ml tube	26
866013	POLYURETHANE SEALANT – NON-SAG • 296 ml tube	26
862032	FASTSET™ ANCHORING EPOXY • 254 ml tube.....	27
990212, 990213	COMMERCIAL GRADE POLYURETHANE ADHESIVE • 300 ml, 858 ml tube.....	27
WATERPROOFING PRODUCTS		
9991060,59,58	XYPEX HIGH 'N DRY • 11 kg, 5 kg, 2.27 kg pail.....	28
9991062, 9991063	XYPEX PATCH 'N PLUG • 2.27 kg, 9 kg pail	28

Data/Spec sheets and Safety Data Sheets (SDS) are available online

<http://www.targetproducts.com/prod-category.aspx>

CONCRETE PRODUCTS

CONCRETE MIX



For general concrete construction and repair of concrete where thickness in excess of 2" is required.

Used for:

- Driveways
- Patios
- Retaining walls
- Footings
- Setting posts
- Sidewalks
- Foundations

Features:

- Consists of cement, sands and coarse aggregates pre-mixed for quality and convenience.
- Approx. 4000 psi (27.6 MPa) in 28 days
- Sets in approximately 4 hours at 20° C (68° F)

Mfr. No. 110125

Ship Weight 25 kg bag | 56 bags/pallet

COVERAGE

25kg Bags required at 4 inch thickness

AREA	1ft	2ft	3ft	4ft
1ft	1	2	3	3
2ft	2	3	5	6
3ft	3	5	7	9
4ft	3	6	9	12
5ft	4	8	12	15

1 x 25kg bag = 0.43 ft³

SONOTUBE	6" diameter	8" diameter	10" diameter	12" diameter
Bags required per 4ft length	1.8	3	5	7.3

POSTHASTE® CONCRETE MIX



A fast setting concrete.

Used for:

- Setting posts
- Signs
- Footings
- Other concrete applications

Features:

- Sets in 20 minutes.
- Eliminates; bracing, construction delays, rain washouts and unwanted depressions
- Approx. 2500 psi (17.2 MPa) in 28 days

Mfr. No. 100465

Ship Wt. 25 kg bag | 56 bags/pallet

COVERAGE

SETTING POSTS (# of bags per hole)

Depth of Hole in Inches (Metres)	19 (.46)	24 (.61)	30 (.76)	36 (.91)	42 (1.07)	48 (1.22)
Post 3" (75mm) Hole Dia. 9" (230mm)	2	2	3	3	4	4
Post 4" (100mm) Hole Dia. 9" (300mm)	2	2	3	3	4	4

1 x 25 kg bag = 0.47 ft³

QUIKRETE® FAST SETTING CONCRETE



A fast setting concrete with fast strength gain.

Used for:

- Setting posts
- Signs
- Slabs
- Footings

Features:

- Set posts without mixing
- Sets hard in 20-40 minutes
- Walk on it in 2 hours
- 1000 psi in 24 hours
- Approx. 4000 psi (27.6 MPa) in 28 days

Mfr. No. 100425

Ship Wt. 25 kg bag | 56 bags/pallet

COVERAGE

SETTING POSTS (# of 25kg (55lb) bags per hole)

Depth of Hole (Inches)	19 (.46)	24 (.61)	30 (.76)	36 (.91)	42 (1.07)	48 (1.22)
Post 3"	2	2	3	3	4	4
Post 4"	2	2	3	3	4	4

SLABS

Square Feet	2 (0.2)	5 (0.5)	10 (0.9)	25 (2.3)	50 (4.7)	100 (9.3)
4" (100mm) Thick	2	4	8	20	40	79
6" (150mm) Thick	3	6	12	30	60	118

All yields are approximate and do not allow for waste or uneven sub-grade, etc. | 1 x 25 kg bag = 0.44 ft³

QUIKRETE® 6000



Construction and repair of concrete where extra strength is required.

Used for:

- Slabs
- Steps
- Patios
- Deck support
- Curbs, Patching existing concrete
- Driveways

Features:

- High strength concrete (6000 psi) (41 MPa) in 28 days.
- Fast strength gain (1 day = 2000 psi).
- Walk on in 8 hours.
- Allows construction in 24 hours
- Withstands higher impact and wears longer than regular concrete
- Less shrinkage

Mfr. No. 100725

Ship Wt. 25 kg bag | 56 bags/pallet

COVERAGE

25kg Bags required at 4 inch thickness

AREA	1ft	2ft	3ft	4ft
1ft	0.75	1.5	2.3	3.0
2ft	1.5	3.0	4.6	6.1
3ft	2.3	4.6	6.9	9.2
4ft	3.0	6.1	9.2	12.3
5ft	3.8	7.7	11.5	15.3

COUNTERTOP MIX



Countertop Mix is a flowable, high strength commercial grade concrete mix designed for use in concrete countertops, requiring only the addition of water.

Used for:

- Countertop Mix is designed specifically for casting concrete countertops.

Features:

- Super-plasticizer additive provides a flowable mix at the low water / cement ratio.
- High-flow formula minimizes the need for mechanical vibration.
- Reduced-shrinkage formulation.
- Approximately 6,000 psi (41 Mpa) in 28 days.

Mfr. No. 110682

Ship Wt. 36.3 kg bag | 42 bags/pallet

COVERAGE

of 36.3 kg bags required

Square Feet (M2)	6 (0.56)	10 (0.93)	25 (2.32)	50 (4.65)
1.5" Thick (37mm) # of 36.3 kg (80lb)	2	3	6	11
2" Thick (50mm) # of 36.3 kg (80lb)	2	3	7	14
3" Thick (75mm) # of 36.3 kg (80lb)	3	5	11	21

SAND / TOPPING MIX



Patching or resurfacing damaged concrete where up to 2" thickness is required.

Used for:

- Driveways, Patios, Sidewalks etc.
- A base for laying flagstone & pavers
- Shower base

Features:

- Consists of cement, fine and coarse sand and admixtures.
- Approx. 4000 psi (27.6 MPa) in 28 days
- Just add water
- Concrete bonding adhesive is required to ensure proper bonding of overlay

Mfr. No. 110326


Ship Wt. 25 kg bag | 56 bags/pallet

COVERAGE

of bags required for 1" or 2" topping

Square Feet (M2)	5 (0.5)	10 (0.9)	20 (1.9)	35 (3.3)	50 (4.7)
1" Thick (25 mm) # of 25 kg (55lb)	1	2	4	7	10
2" Thick (50mm) # of 25 kg (55lb)	2	4	8	14	20

PORTLAND EXPANDING GROUT



A high-strength non-shrink grout used for the following applications.

Used for:

- Grouting under columns and base plates
- Anchoring of posts and bolts into concrete
- Filling voids and cracks
- Repair to concrete structures

Features:

- High strength – up to 8800 psi (60.5 MPa)
- 3200 psi (22 MPa) in 24 hours
- Non-shrink
- Up to 6" in thickness

Mfr. No. 158556

Ship Wt. 22.7 kg bag | 56 bags/pallet

COVERAGE

No of 22.7 kg bags required for 1" or 2" topping

Square Feet (M2)	5 (0.5)	10 (0.9)	20 (1.9)	35 (3.3)	50 (4.7)
1" Thick (25mm) # of 25 kg (55lb)	1	2	4	7	10
2" Thick (50mm) # of 25 kg (55lb)	2	4	8	14	20

COMMERCIAL GRADE FASTSET™ MORTAR REPAIR



QUIKRETE FastSet Repair Mortar is a rapid setting structural mortar for repairing all concrete surfaces including vertical and overhead applications.

Uses:

- Walls
- Bridges
- Tunnels
- Sewers, culverts
- Columns

Features:

- Superior bonding
- Sets in 20 minutes
- High strength 2000 PSI (13.8 Mpa) in 3 hours
- 6000 PSI (41.4 MPa) in 28 days

Mfr. No. 124152

Ship Wt. 22.7 kg bag | 30 bags/pallet

COVERAGE

No of 22.7 kg (50 lb) bags

Thickness	2 (0.2)	5 (0.5)	10 (0.9)	15 (1.4)	20 (1.8)	50 (4.6)
1" (25mm)	1	1	2	3	4	9
2" (50mm)	1	2	4	5	6	17
*3 (75mm)	1	2	4	6	8	10
4 (100mm)	1	3	5	8	11	26

* Extended with 11.34 kg (25 lbs) ½" (12 mm) gravel per bag.

COMMERCIAL GRADE FASTSET™ ALL-CRETE™



QUIKRETE FastSet All-Crete is a fast setting non-shrink structural grout for concrete construction and repair.

Uses:

- Anchor bolts
- Bearing plates
- Floor leveling and repair
- Precast concrete keyways
- Steel column bases
- Roads and bridges
- Filling voids and cracks.

Features:

- Structural concrete repairs from 1/4" to 24" deep
- Sets in 30 minutes
- Mix to fluid flowable and plastic consistency
- Up to 8000 PSI (55.1 MPa) in 28 days

Mfr. No. 158553

Ship Wt. 22.7 kg bag 30 bags/pallet

COVERAGE

No of 22.7 kg (50 lb) bags

Thickness	2 (0.2)	5 (0.5)	10 (0.9)	15 (1.4)	20 (1.8)	50 (4.6)
1" (25mm)	1	1	2	3	4	9
2" (50mm)	1	2	4	5	6	17
*3 (75mm)	1	2	4	6	8	10
4 (100mm)	1	3	5	8	11	26

* Extended with 11.34 kg (25 lbs) 1/2" (12 mm) gravel per bag.

MASONRY PRODUCTS

MASON MIX (TYPE S MORTAR)



Contractor grade, type 'S', pre-blended mortar.

Used for:

- Brick construction
- Stone construction
- Repairing mortar joints
- Block construction
- Base coat for stucco

Features:

- Pre-blended, just add water
- High strength
- Exceeds ASTM C270 requirements

Mfr. No. 113655

Ship Wt. 25 kg bag | 56 bags/pallet

COVERAGE

1 bag lays 40 bricks

1 bags lays 18 standard blocks (16" x 8" x 8")

1 bags = 22 sq ft of base coat at 1/4" thick

WATER RESISTANT PARGING MIX



Masonry coating and patching of concrete walls for cosmetic purposes.

Used for:

- Concrete block
- Concrete & masonry walls
- Base coat for stucco

Features:

- Easy to apply
- Strong bond
- Resists water penetration
- Can be applied above and below grade

Mfr. No. 115525

Ship Wt. 25 kg bag | 56 bags/pallet

COVERAGE

No of 25 kg (55 lb) bags

Square Feet (M ²)	25 (2.3)	50 (4.7)	300 (27.9)	500 (46.5)	1000 (92.9)
1/8" thick (3 mm)	1	2	8	13	25
1/4" thick (6mm)	3	4	15	25	50

All yields are approximate and do not allow for waste or uneven sub-grade, etc.

QUIKWALL SURFACE BONDING CEMENT - GRAY



QUIKWALL Surface Bonding Cement is a premium resurfacing product.

It eliminates the need for mortar in block wall construction.

Used for:

- Surface bonding and resurfacing of concrete and masonry walls

Features:

- Strengthens and waterproofs block walls without mortar
- Superior bond
- Interior and exterior use

Mfr. No. 123151

Ship Wt. 22.7 kg bag | 35 bags/pallet

COVERAGE

No of 22.7 kg (50 lb) bags

Square Ft (M ²)	25 (2.3)	50 (4.7)	300 (27.9)	500 (46.5)	1000 (92.9)
1/8" thick (3 mm)	1	1	6	10	20
1/4" thick (6 mm)	1	2	12	20	40

All yields are approximate and do not allow for waste or uneven sub-grade, etc.

CEMENTS AND LIME

GENERAL USE CEMENT



Normal Portland Cement is a basic ingredient for general purpose concrete

Used for:

- General purpose concrete

Features:


- Just add: fine aggregate, coarse aggregate and clean water
- Easy to transport to remote area

Mfr. No.	112425	405942
Ship Wt.	40 kg bag	20 kg bag
	40 bags/pallet	72 bags/pallet

Mix Proportions for Concrete Mix:

CONCRETE STRENGTH	CEMENT	WATER (1)	FINE AGGREGATE (2) (DAMP)	COARSE AGGREGATE (3)	VOLUME
20 MPa	1 bag 40 kg	24 L	140 kg	125 kg	0.14m3 (5 cu. Ft)
25 MPa	1 bag 40 kg	22 L	115 kg	120 kg	0.13m3 (4.5 cu. Ft)
30 MPa	1 bag 40 kg	20 L	105 kg	110 kg	0.12m3 (4.2 cu. Ft)
32 MPa (with air entrainment) **	1 bag 40 kg	18 L	95 kg	100 kg	0.11m3 (3.8 cu. Ft)

MCS (MORTAR S) CEMENT



Mortar S Cement, is a type 'S' cement.

Used for:

- Making: Stucco-finish, Base Coat, Mortars, Parging and other masonry applications.

Features:

- Mortar S Cement only requires the addition of sand and water for masonry applications

Mfr. No. 112532

Ship Wt. 30 kg bag | 40 bags/pallet

COVERAGE

Mix 1 - 30 kg bag mortar cement with 2 ¼ to 3 parts loose, damp sand for mortar applications

HE (TYPE 30) PORTLAND CEMENT



Type HE is a High Early Strength Portland Cement.

Used for:

- Applications where high early strengths are required

Mfr. No. 112479

Ship Wt. 40 kg bag | 40 bags/pallet

HS (TYPE 50) PORTLAND CEMENT



LAFARGE Type HS Portland Cement

Used for:

- Applications that require high levels of sulphate resistance.

Mfr. No. 9994022, 9994005

Ship Wt. 20 kg bag | 72 bags/pallet
40 kg bag | 40 bags/pallet

WHITE PORTLAND CEMENT | FEDERAL WHITE



White Portland Cement Type I is a true Portland cement

Used for:

- White or colouring applications.
- Federal White Cement can be used for all types of architectural or structural concrete construction where a whiter or brighter color may be needed for aesthetic or safety reasons.
- Federal White Cement may also be used to satisfy low alkali requirements.

Mfr. No. 9994010

Ship Wt. 42 kg bag | 40 bags/pallet

PORTLAND CEMENT LIME BLEND



TARGET Portland Cement Lime Blend is used for making mortars - ensuring uniformity during construction. It is prepared under tight quality control standards to ensure consistency.

Used for:

- TARGET Portland Cement Lime Blend yields high strength mortar

Features:

- TARGET Portland Cement lime mortars exhibit superior bond characteristics, less shrinkage and cracking than other mortars resulting in greater resistance to water penetration.

Mfr. No. 405951

Ship Wt. 30 kg bag | 50 bags/pallet

HYDRATED LIME – TYPE 'S'



Used for:

- Mixing with cement and sand to make mortar, stucco and other masonry products
- Agricultural use


Features:

- Fine Grade

Mfr. No. 9994028

Ship Wt. 23 kg bag | 50 bags/pallet

HYDRATED LIME – TYPE 'N'



Used for:

- Mixing with cement and sand to make mortar, stucco and other masonry products
- Agricultural use

Features:

- Fine Grade

Mfr. No. 9994035

Ship Wt. 22.68 kg bag | 50 bags/pallet

REPAIR PRODUCTS - BAGS

BONDED TOPPING MIX



Concrete repair material designed for thin overlays and repair of concrete up to 1/2".

Used for:

- Overlays
- Levelling
- Damaged and cracked concrete

Features:

- High strength
- Strong bond
- 90 minute set
- Foot traffic in 2.5 hours
- Trowels to a featheredge

Bag Mfr. No. 113318

Ship Wt. 18 kg bag | 56 bags/pallet

COVERAGE

1 – 18 kg bag = 18 ft sq at 1/4" thickness

RECAP™ RESURFACER



A special blend of portland cement, sand, polymer modifiers and other additives. Designed to provide a shrinkage compensated repair material for making thin repairs to sound concrete in need of surface renewal. Can be squeegee, trowel or brush applied.

Used for:

- Sidewalks
- Concrete Floors
- Patios
- Floors
- Pool Decks
- Driveways
- Parking Decks
- Curbs

Mfr. No. 113148

Ship Weight 18 kg bags 56 bags / pallet

COVERAGE *

Squeegee Application

Square Feet (m ²)	35 (3.3)	90 (8.4)	200 (18.6)	300 (27.9)	500 (46.5)
1/16" (1.5mm) thick # of bags	1	2	3	4	7

Thicker Application

1/8" (3mm) thick # of bags	1	3	6	9	14
1/4" (6mm) thick # of bags	2	5	11	17	27
3/8" (9mm) thick # of bags	3	7	15	23	39

* All yields are approximate and do not allow for waste or uneven sub-grade, etc.

FAST-SET SELF-LEVELING FLOOR RESURFACER



COVERAGE

1 – 22.7 kg bag = 14 L (0.50 cu)
At 6.4 mm (1/4") thick each bag will cover
approx. 2.3 m² (25 ft²) of flat surface

QUIKRETE New & Improved Fast-Setting Self-Leveling Floor Resurfacer is a self-finishing floor topping and underlayment specially formulated to work without troweling.

Used for:

- Precast concrete plank
- New concrete floor slabs with unacceptable finishes
- Existing concrete floors with damaged finishes
- Over wood floor systems, utilizing expanded metal lath reinforcement
- May be used for outdoor service

Features:

- Can be used as a wear surface for light industrial floors.
- Works without troweling.

Mfr. No. 124958

Ship Wt. 22.7 kg bag | 35 bags/pallet

BLACK TOP PATCH



COVERAGE

1 bag covers 2 sq ft at 2" thickness

Blacktop Patch is an asphalt cold patch for repairing pot holes and large cracks over 25 mm (1 inch).

Used for:

- Asphalt pavements such as driveways
- Parking lots
- Roads
- Playground and pathways

Features:

- Ready to use
- No mixing or heating required
- Traffic can begin immediately after levelling and compacting

Mfr. No. 170125

Ship Wt. 25 kg bag | 30 bags/pallet

SANDS AND AGGREGATE PRODUCTS

PREMIUM PLAY SAND



A versatile sand.

Used for:

- Children's sandbox
- Traction for snowy and icy surfaces
- Base and between joints for concrete pavers
- Lawn and garden conditioner

Features:

- Heat sterilized
- Washed and screened
- Free of most dust

Mfr. No. 111325

Ship Wt. 25 kg bag | 48 bags/pallet

COVERAGE

1 bag = ½ cubic ft (12" x 12" x 6" thick)

ALL PURPOSE GRAVEL



Multi use gravel for decorative and landscaping applications.

Used for:

- Landscaping
- Drainage
- Window wells
- Fish ponds
- Concrete

Features:

- Easy to pour
- Easy to store
- Easy to transport
- Durable plastic bag

Mfr. No. 115125

Ship Wt. 25 kg bag | 30 bags/pallet

COVERAGE

1 bag = ½ cubic ft

BASE ROCK



COVERAGE

1 bag = ½ cubic ft

A levelling base for masonry products and other applications.

Used as a base for:

- Pavers
- Flagstone
- Brick
- Retaining walls
- Walkways and Driveways

Features:

- Saves time
- Professional quality
- Easy to use
- Durable plastic bag

Mfr. No. 115155

Ship Wt. 25 kg bag | 30 bags/pallet

PATIO PAVER JOINTING SAND



COVERAGE

36 kg (80 lb) bag = 7 to 9 m² (75 to 100 ft²)

Properly graded fine sand for filling joints between pavers, flagstone and other masonry products.

Used for:

- Patios
- Sidewalks
- Driveways

Features:

- Washed and dried
- Properly screened
- Angular for stability
- Durable plastic bag

Mfr. No. 115036

Ship Wt. 36 kg bag | 42 bags/pallet

TRACTION SAND



Ideal for traction on all surfaces in icy conditions.

Used for:

- Icy and snowy surfaces
- Added vehicle weight

Features:

- Re-usable poly bag
- Angular
- Easy to pour

Mfr. No. 115831

Ship Wt. 18 kg bag | 48 bags/pallet

SILICA ABRASIVE 30-50, 16-30, 12-40, 12-50, 20-40



TARGET® Silica Abrasives are high quality, close graded silica sands which undergo up to three washings to provide a clean, high quality material.

Uses:

- Target Silica Abrasives are suitable for sandblasting of steel, concrete or wood in preparation for coating or repair, to obtain architectural effects in concrete or wood, an aggregate for cementitious or polymer grouts, mortars and concrete and for foundry mold sand and traction sand.

Mfr. No. 99933050, 99931630, 99931240, 99931212, 99932040

Ship Wt. 22.7 kg bag | 72 bags/pallet

1/4 DOWN – LIMESTONE



1/4" Down-Limestone provides a firm, stable, foundations for interlocking pavers, flagstone, bricks, patio block, concrete slabs and anchoring of posts.

Used for:

- Paver base
- Walkway base
- Concrete slab base
- Setting Posts

Features:

- Great compaction
- Easy to store
- Easy to transport
- Durable plastic bag
- Only available from Winnipeg Plant

Mfr. No. 116036

Ship Wt. 25 kg bag | 30 bags/pallet

COVERAGE

1 bag = 1/2 cubic ft

EARTH ESSENTIALS - SAND




PLAY SAND
 Mfr. No. 137550
 Ship Wt. 18 kg bag | 70 bags/pallet



POLYMERIC JOINTING SAND
 Mfr. No. 137556
 Ship Wt. 18 kg bag | 70 bags/pallet

EARTH ESSENTIALS - STONES, PEBBLES & ROCKS



LIMESTONE SCREENINGS
 Mfr. No. 137546
 Ship Wt. 18 kg bag | 70 bags/pallet



BEACH PEBBLES
 Mfr. No. 137517
 Ship Wt. 18 kg bag | 70 bags/pallet



RED CRUSHED TILE
 Mfr. No. 137530
 Ship Wt. 18 kg bag | 70 bags/pallet



PEA GRAVEL
 Mfr. No. 137510
 Ship Wt. 18 kg bag | 70 bags/pallet



WHITE ROCK
 Mfr. No. 137504
 Ship Wt. 18 kg bag | 70 bags/pallet



DRAINAGE GRAVEL
 Mfr. No. 137520
 Ship Wt. 18 kg bag | 70 bags/pallet

MISCELLANEOUS PRODUCTS

QUIK-TUBE® BUILDING FORMS




The QUIK-TUBE® Building Forms are ridged fibre building form tubes that eliminate the need to build wood forms.

Used for:

- Mailbox bases
- Deck supports
- Columns

Dia. x Length	6" x 8'	8" x 8'	10" x 8'	12" x 8'
Mfr. No.	692316	692251	692252	692253
Min Order	3	4	4	4

WALK MAKER® BUILDING FORM



692132 • Country Stone Pattern

Reusable plastic moulds. Fill the mould with concrete mix (approx 1 ½ bags of 25 kg concrete mix fills 1 mould), trowel, and remove the mould. For best results use QUIKRETE® 6000.

Used for:

- Walkways
- Garden Paths
- Patios
- Courtyards

Features:

- Customize the color with QUIKRETE® Liquid Cement Colors

COVERAGE

Approx. 1 ½ bags of 25 kg QUIKRETE 6000 concrete mix to one mould.

Mfr. No. 692132 – Country Stone Pattern

Available: 1 pc 2' x 2' x 2" | 6 per case

LIQUID CEMENT COLOUR



COVERAGE

Will colour up to 2 – 25 kg (55 lb) bag of Concrete, Mortar, or Sand Mix

More intense colour can be achieved by using additional Cement Colour. Do not use more than one bottle per 25 kg (55lb)

A liquid coloring agent used to customize the color of your concrete project.

Add correct amount of dry concrete mix or mortars to water for a proper consistency. One bottle will mix with two 25kg (55lb) bags of Concrete Mix. Available in Red, Brown, Buff, Charcoal.

Used for:

- Adding color to Walk Maker™ projects
- Adding color to any concrete, mortar, sand topping or stucco project
- Permanent integral color

Features:

- Add colour to a variety of projects including: curbs, driveways, fishponds, and stucco
- Available in 4 colours

Mfr. No.	131720	131721	131722	131723
Colour	Charcoal	Brown	Buff	Red
Ship Wt. 296 ml - 12 bottles/case				

BACKER ROD



A foam rope used to partially fill large cracks, gaps and joints before applying sealant. Use for horizontal and vertical applications.

Used for:

- Expansion joints
- Curtain wall joints
- Partitions
- Log construction
- Pavement joints
- Pre-cast units

Features:

- Backer Rod can be used as a temporary seal, or inserted into a joint to control sealant depth
- To create a backstop
- Allows for tooling of sealant
- Allows for proper wetting of the joint surfaces for sealing

Mfr. No. 691741

1 piece 3/4" dia. X 20' | 12 per case

EXPANSION JOINT STRIPS



Made from resilient wood fibers to prevent damage during expansion and contraction of concrete. Weather resistant.

Used for:

- Driveways, sidewalks and patios
- Between concrete slabs and to separate slabs from structures

Mfr. No. 691706

Available in: 5' long strips | 40 strips per carton

ACRYLIC FORTIFIER



An acrylic resin admixture designed to enhance bonding and water resistance of concrete patching materials, stucco, surface bonding cement, thin-set mortars and tile grouts. Exceeds the requirements of ASTM C 1438

Used for:

- Improves bonding to existing surfaces
- Eliminates moist curing in most circumstances
- Reduces permeability

Features:

- Increases bond
- Strengthens concrete
- Helps protect concrete from environment

Mfr. No. 861016

Ship Wt. 0.95L bottle - 6 per case

MIXING

Shake well before using.

Use the recommended amount of Concrete Acrylic Fortifier along with sufficient water to provide proper consistency

For QUIKRETE® Quick-Setting Cement & QUIKWALL® Surface Bonding Cement, add 1.9 L of Concrete Acrylic Fortifier per 22.7 kg bag

CONCRETE & ASPHALT CLEANER - CONCENTRATE



A multi-purpose cleaner that is safe to use on any hard surface where water can be used. Use prior to any repair project to achieve the strongest bond. Non-toxic, non-flammable and contains no acid.

Used for:

Removing soil grease, oil, etc. from all types of masonry, concrete, mortar and grout

Cleans:

- Brick
- Slate
- Flagstone
- Quarry tile
- Driveways
- Grout in ceramic tile
- Parking lots
- Garage floors
- Gas stations
- Industrial plant floors
- Tools and Lawnmowers

Mfr. No. 860112

Ship Wt. 946 ml | 6 per case

APPLICATION

Light soil: One part to 6 parts fresh water.

Medium soil: One part to 4 parts fresh water

Heavy soil: Dilute 1:1 or use full strength.

ACRYLIC CONCRETE CURE & SEAL (SATIN)



Concrete sealer is used for curing, protecting and sealing concrete surfaces.

Used for:

- Curing new concrete
- Protects concrete against water, salt, oils etc.
- Protects concrete against graffiti on concrete walls
- Protects concrete from environment

Features:

- Attractive satin look
- Makes surface easier to clean
- Can be sprayed, broomed or roller applied

Mfr. No. 873102

Ship Wt. 3.8 L | 4 pails/case

COVERAGE

1 x 3.8 L = 14-18 m² (150-200 ft²).

REPAIR PRODUCTS – PATCHING PRODUCTS

BONDED TOPPING MIX



COVERAGE

1-4.5 kg pail = 3¼ ft sq at ¼" thickness

Concrete repair material designed for thin overlays and repair of concrete up to 1/2".

Used for:

- Overlays
- Levelling
- Damaged and cracked concrete

Features:

- High strength
- Strong bond
- 90 minute set.
- Foot traffic in 2.5 hours
- Trowels to a featheredge

Mfr. No. 113304

Ship Wt. 4.5 kg pail | 4 pails/case

HYDRAULIC WATER STOP CEMENT



COVERAGE

1 x 4.5 kg pail will fill a crack ½" W x 1 ½" D x 15' L

Rapid setting, high strength repair material designed to plug active water leaks instantly in concrete and masonry.

Used for:

- Basement walls
- Retaining walls
- Swimming pools
- Instant anchoring
- Foundation walls

Features:

- High strength (2000 psi (13.8 MPa) in 30 minutes)
- 3-5 minute set


Mfr. No. 112612

**Ship Wt. 4.5 kg pail
4 pails/case**

112606

9 kg pail

ANCHORING CEMENT



COVERAGE

Each 4.5 kg pail will yield approximately 0.08 cu ft (2.4 L)

Rapid setting grout.

Used for:

- Anchoring of posts, rails and bolts in concrete
- Filling of cracks and voids
- Patching concrete

Features:

- High strength (2000 psi (13.8 MPa) in 2 hours, 7000 psi (48.3 MPa) at 28 days)
- Fast setting (10-30 minutes)
- Flowable

Mfr. No. 124512

Ship Wt. 4.5 kg pail | 4 pails/case

QUICK-SETTING CEMENT



For concrete repairs where rapid setting is required.

Used for:

- Steps
- Curbs
- Walls
- Overhead

Features:

- Sets fast (10-15 minutes)
- High strength, strong bond
- Can be applied horizontally, vertically and overhead
- Can be molded or sculpted

Mfr. No. 124012

Ship Wt. 4.5 kg pail | 4 pails/case

CONCRETE BONDING ADHESIVE



Permanently bonds new concrete to existing concrete.

Used for:

- Bonding new concrete to old concrete
- Bonding new plaster and stucco to old plaster and stucco

Features:

- Indoor/Outdoor application
- Apply by brush roller or spray to the thickness of a coat of paint
- Concentrated

Mfr. No.	990203	990216
Ship Wt.	3.8L bottle 4 per case	0.95L bottle 6 per case

COVERAGE

Paint-on application 14-28 m² (150-300 ft²) per 3.8 L

Slurry coat application 7 m² (75 ft²) per 3.8 L

CONCRETE PATCHING COMPOUND



A ready-to-use concrete repair for making repairs to cracks, holes and breaks (up to 1/4" wide) in concrete, stucco or masonry walls, sidewalks, patios, driveways, etc.

Used for:

- Repairs and fills spalls (surface imperfections) and cracks up to 1/4" (6 mm) deep in concrete, masonry, stucco, sidewalks, patios, walkways and steps.

Features:

- No mixing required
- Dries quickly to a durable and flexible finish
- Weather resistant
- Excellent adhesion
- Textured to blend with concrete surfaces
- Easy clean up with water before product dries
- Use for non-structural cosmetic repairs

COVERAGE

3.25 sq ft (0.3 M²) at a 1/8" (3 mm) thickness.

Mfr. No. 865036

Ship weight: 946 ml | 12 per case

ZIP AND MIX REPAIR MORTAR



COVERAGE

Each 1.36 kg bag will yield 0.03 cubic feet of material

ZIP AND MIX Repair Mortar is a structural mortar repair.

Used for:

- Repairing concrete, masonry and stucco surfaces up to 2 inches in thickness. It can be used on driveways, sidewalks, patios, steps, concrete and masonry walls.

Features:

- Just add water to bag, mix and apply
- Use on vertical and horizontal surfaces
- Superior bonding
- 4500 psi (31.3 MPa) in 28 days

Mfr. No. 124116

Ship Wt. 1.36 kg bag | 6 bags per case

PRE-MIXED STUCCO PATCH



COVERAGE

Each 0.95 L (1 qt) pail will cover approx 3.25 sq. ft (0.3 M²) at 1/8" (3 mm) thickness.

A ready-to-use acrylic stucco repair.

Used for:

- Making repairs to cracks, breaks and holes up to 1/4" (6 mm) thick in stucco surfaces.

Features:

- Dries to a durable and flexible finish
- Sanded formula blends with the texture of surrounding stucco

Mfr. No. 865033

Ship Wt. 0.95 L pail | 12 pails / case

EXTERIOR STUCCO PATCH



COVERAGE

4.5 kg pail yields 5 m² (6 ft²) @ 1/4"

A finish coat stucco.

Used for:

- Repairing broken, cracked or damaged stucco.

Features:

- White in colour
- Resistant to shrinkage cracks
- Can be textured and colored to match existing stucco
- Paintable

Mfr. No. 120145

Ship Wt. 4.5 kg pail | 4 pails/case

REPAIR PRODUCTS – JOINT AND CRACK REPAIR

GREY CONCRETE CRACK SEALER



A latex formulation designed to adhere to horizontal concrete surfaces.

Used for:

- Repairing cracks in concrete
- Sidewalks
- Patios
- Driveways

Features:

- Flows well into cracks
- Easy to apply

Mfr. No. 864002

Ship Wt. 946 ml squeeze bottle | 6 per case

COVERAGE

946 ml fills approximately: 18 m (60 ft)
of crack at 1/4" x 1/4"

CONCRETE REPAIR



A superior sanded acrylic latex formulation for crack repair in concrete, including concrete, stucco or masonry walls, sidewalks, patios and driveways.

Used for:

- Repairing and filling cracks up to 12 mm (1/2") in concrete, masonry, stucco, sidewalks, patios and driveways
- Vertical or horizontal surfaces

Features:

- Dries quickly to a tough and flexible finish
- Helps prevent water and ice damage to concrete surfaces
- Weather resistant
- Excellent adhesion
- Textured to blend with concrete surfaces
- Easy clean up with water before product dries

Mfr. No. 862012

Ship Wt: 296 ml | 12 tubes/case

COVERAGE

296 ml tubes will yield about 7.3 m at a 6 mm (1/4")
diameter bead or 3.7 m (12 lineal feet) for a 9 mm
(3/8") diameter bead

STUCCO CRACK REPAIR



Stucco Crack Repair is an easy to use crack repair for stucco.

Used for:

- Filling and sealing cracks in stucco up to 12 mm (1/2")

Features:

- Blends with texture of surrounding stucco
- Paint after 24 hours
- Works on horizontal and vertical surfaces
- Excellent adhesion

Mfr. No. 865011

Ship Wt. 296 ml | 6 tubes / case

COVERAGE

Each 296 ml tube will yield 3.7 m (12 linear feet) at 6 mm (1/4") bead.

MORTAR REPAIR



Acrylic repair for mortar joints.

Used for:

- Re-pointing and repairing mortar joints
- Concrete crack repair

Features:

- Square applicator tip for easy application
- Flexible
- Strong bond
- Mortar grey
- Fits standard caulking gun

Mfr. No. 862002

Ship Wt. 296 ml | 6 tubes/case

COVERAGE

One cartridge fills 10 ft of 3/8" x 3/8" voids

FIREPLACE MORTAR



A silicate based refractory cement caulk

Used for:

- Tuck-pointing damaged fireplace mortar joints
- Repairing cracked or chipped firebricks in fireplaces and wood-burning stoves.

Features:

- Fireplace Mortar provides excellent adhesion and when exposed to fire is strengthened to firebrick hardness.
- Meets ASTM E 136-04
- Fireplace safe to 1093°C (2000°F)
- As strong as fire brick
- Easy clean-up while wet

Mfr. No. 862025

Ship Wt. 296 ml tube | 12 tubes per case

COVERAGE

Approximately 100 linear ft. (30.5 m) for a 1/8" (3 mm) diameter bead

POLYURETHANE MORTAR JOINT SEALANT



Polyurethane Mortar Joint Sealant is a high performance construction grade polyurethane sealant.

Used for:

- Waterproofing and sealing mortar joints and bonds to most construction materials.

Features:

- Excellent adhesion
- Non-sag formulation
- Dries to touch in 2 hours
- Flexible

Mfr. No. 862019

Ship Wt. 296 ml | 12 tubes/case

COVERAGE

Each 10.1 oz (300 ml) tube can be applied to approximately 12 linear feet (3.7 m) in a 3/8" (10 mm) bead

POLYURETHANE SEALANT GRAY – SELF LEVELLING



Polyurethane Self-Levelling Sealant is a high performance construction grade polyurethane sealant.

Used for:

- Sealing cracks and joints in horizontal concrete surfaces. It can be used for concrete floors, driveways, patios, steps, basements, pool decks and more.

Features:

- Superior adhesion
- Durable and flexible
- Resistant to moisture
- Virtually no shrinkage

Mfr. No. 866012

300 ml tube | 12 tubes / case

Mfr. No. 866032

858 ml tube | 6 tubes / case

COVERAGE

12 linear feet (3.7 m) at ½" x ¼" (12 x 6 mm) joint

POLYURETHANE SEALANT – NON-SAG



A high performance, construction grade polyurethane sealant designed for vertical and overhead surfaces.

Used for:

- Vertical or horizontal expansion joints in concrete, stucco or masonry
- Caulking around window and door openings
- Sealing skylights and chimney flashings

Features:

- The non-sag formula provides superior adhesion and flexibility. Meets ASTM C 920, Type S, Grade NS.

Mfr. No. 866013

Ship Wt. 296 ml tube | 12 tubes / case

COVERAGE

12 linear feet (3.7 m) at ½" x ¼" (12 x 6 mm) joint

FASTSET™ ANCHORING EPOXY



FASTSET™ Anchoring Epoxy is a commercial grade, fast-setting, two component structural epoxy.

Used for:

- Anchoring such things as bolts, rebar, railings, threaded rod, etc, in concrete, masonry and rock.

Features:

- Sets fast (in 3-4 minutes)
- High strength
- Non-sag
- For vertical and horizontal applications
- Sets in sub-zero temperatures

Mfr. No. 862032

Ship Wt. 254 ml tube | 6 tubes / case

COVERAGE

Each 254 ml tube will yield 3.2 m (0.3 linear feet) at 6 mm (1/4") bead.

COMMERCIAL GRADE POLYURETHANE ADHESIVE



Commercial Grade Adhesive is a high performance, construction grade adhesive.

Used for:

- Permanently bonding concrete masonry and all types of construction materials such as wood, glass, metal and plastic.

Features:

- Superior bond
- Water resistant
- Freeze/thaw resistant
- Flexible

Mfr. No. 990212

Ship Wt. 300 ml | 12 per case

Mfr. No. 990213

Ship Wt. 858 ml | 6 per case

COVERAGE

Each 300 ml tube can be applied to approximately 12 linear feet (3.7 m) in a 3/8" (10 mm) bead

WATERPROOFING PRODUCTS

XYPEX HIGH 'N DRY



For permanent waterproofing of concrete.

Used for:

- Basement walls
- Retaining walls
- Concrete ponds

Features:

- Penetrates deep into concrete
- Withstands water pressures
- Easy to apply
- Works under wet conditions
- Can be applied to the inside or outside of basement walls

Mfr. No.	9991058	9991059	9991060
Ship Wt.	11 kg pail	5 kg pail	2.27 kg pail
	1 per case	1 per case	6 per case

COVERAGE

1 lb = 6 square feet

XYPEX PATCH 'N PLUG



A specially designed, fast setting, non-shrink, high-bond-strength, hydraulic cement compound for concrete patching and repair. Patch 'n Plug stops flowing water in seconds and is used to seal cracks, tie holes, and other defects in concrete.

Used for:

- Basements walls
- Retaining walls
- Swimming pools
- Instant anchoring
- Foundation walls

Features:

- High strength (2000 psi in 30 minutes)
- 3-5 minutes set
- Non metallic. Non toxic

Mfr. No.	9991062	9991063
Ship Wt.	2.27 kg pail	9 kg pail
	6 per case	1 per case

COVERAGE

1 lb = 6 square feet

CONTACT INFORMATION



FOR TECHNICAL SALES & ASSISTANCE | CEMENT & CONCRETE PRODUCTS

SALES REPRESENTATIVES

Mike Coghill	Tel: 1 204 654 8320	Email: mike.coghill@quikrete.ca
Mara Marsden	Tel: 1 604 417 2188	Email: mara.marsden@quikrete.ca
Brent Foster	Tel: 1 403 471 0529	Email: brent.foster@quikrete.ca
Tammy-Lee Klassen	Tel: 1 403 690 2185	Email: tammy-lee.klassen@quikrete.ca

CORPORATE SALES OFFICE: Tel: 1 604 444 3620 Fax: 1 604 420 3616

8535 Eastlake Drive
Burnaby, BC
Canada V5A 4T7

Toll Free: 1 800 575 7700

PLANT LOCATIONS

VANCOUVER PLANT: Tel: 1 604 856 7976 Fax: 1 604 856 7972
1080 Bradner Road Toll Free: 1 888 484 1258 Orders: Abbotsford.Order@Quikrete.ca
Abbotsford, BC
Canada V4X 1H8

Mara Marsden Tel: 1 604 417 2188 Email: mara.marsden@quikrete.ca

CALGARY PLANT: Tel: 1 403 279 8189 Fax: 1 403 279 4829
5150 90 Avenue, SE Toll Free: 1 800 661 8482 Orders: Calgary.Order@Quikrete.ca
Calgary AB
Canada T2C 2T2

Brent Foster Tel: 1 403 471 0529 Email: brent.foster@quikrete.ca
Tammy-Lee Klassen Tel: 1 403 690 2185 Email: tammy-lee.klassen@quikrete.ca

WINNIPEG PLANT: Tel: 1 204 654 8320 Fax: 1 204 654 8329
400 Pandora Avenue W Toll Free: 1 855 654 8320 Orders: WinnipegOrder@Quikrete.ca
Winnipeg MB
Canada R2C 3A5

Mike Coghill Tel: 1 204 654 8320 Email: mike.coghill@quikrete.ca

