

# TARGET BLOCK FILL GROUT

June, 2019 Page 1 of 2

## PRODUCT DESCRIPTION

TARGET® Block Fill Grout is a dry, preblended mix containing cementitious materials and dried aggregates. It is formulated to provide superior flow to fill masonry voids and meets ASTM C476, CSA 179 requirements for reinforced masonry construction. TARGET Block Fill Grout is designed as a fluid cementitious material and is used to bond adjacent masonry units and steel reinforcement in the cores of the masonry units to the masonry assemblage, and to fill reinforced bond beams.

Using TARGET Block Fill Grout in conjunction with existing reinforcement will produce a structurally sound final wall system for reinforced masonry construction.



## ADVANTAGES

- Batch-to-batch consistency
- Laboratory tested mix designs, per ASTM C476, CSA 179
- Preblended to minimize labour costs
- Complements any grout placement system
- Eliminates demurrage charges
- No minimum load requirements
- Dependable availability
- No sand pebbles or wasted materials

## COMPOSITION & MATERIALS

TARGET Block Fill Grout contains Portland cement, pozzolans and dried aggregates.

## PREPARATORY WORK

TARGET Block Fill Grout may be used in both low-lift and high-lift applications. Special consideration should be given when selecting the type of grout for a particular application. Handle and store product according to Target Products Ltd. recommendations. Target Products Ltd. products are custom packaged to the specification and must be stored dry, covered and protected from weather and other damage.

**NOTICE:** Obtain the applicable **LIMITED WARRANTY** at [www.targetproducts.com/product-warranty](http://www.targetproducts.com/product-warranty)  
Or send a written request to Target Products Ltd., Five Concourse Parkway, Atlanta, GA 30328, USA.  
© Quikrete Canada Holdings, Limited. Manufactured by Target Products Ltd. ©2019 Quikrete International, Inc.



T  
A  
R  
G  
E  
T  
  
P  
R  
O  
D  
U  
C  
T  
S  
  
L  
T  
D

# TARGET BLOCK FILL GROUT

June, 2019 Page 2 of 2

## METHODS

TARGET Block Fill Grout may be placed by hand or by mechanical delivery. It should be consolidated upon placement and reconsolidated before initial set.

## MIXING

When mixing, use a mechanical batch mixer to ensure homogeneity, and workability. Use clean, potable water, and add the maximum amount consistent with optimum workability. Mixing time is 5 minutes and should be consistent from batch to batch. Hand mixing of the grout should be permitted only with the written approval by the specifier, who must outline hand mixing procedures.

## CURING

TARGET Block Fill Grout should be cured a minimum of 28 days. Unused grout should be discarded one-and one-half hours from initial mixing.

## BUILDING CODES

TARGET Block Fill Grout should be installed in accordance with the provisions of the local building codes. These products should also be installed in accordance with the instructions and requirements provided by the manufacturer of the precast stone or brick.

## PACKAGING

TARGET Block Fill is available in 36 kg (80 lb) bag 42 bags /pallet or 1360 kg bulk bags 1/pallet.

**NOTICE:** Obtain the applicable **LIMITED WARRANTY** at [www.targetproducts.com/product-warranty](http://www.targetproducts.com/product-warranty)  
Or send a written request to Target Products Ltd., Five Concourse Parkway, Atlanta, GA 30328, USA.  
© Quikrete Canada Holdings, Limited. Manufactured by Target Products Ltd. ©2019 Quikrete International, Inc.



T  
A  
R  
G  
E  
T  
  
P  
R  
O  
D  
U  
C  
T  
S  
  
L  
T  
D