

DRYMIX BRAND **PARGING MIX**

June 2019 Page 1 of 2

PRODUCT

DRYMIX PARGING MIX is a strong formulation with a finish texture that enables direct bonding to **clean concrete**.

DRYMIX PARGING MIX does not bond to anything but clean, porous cement based mixtures. It is important to clean the concrete base of form release oils, dirt or tar to provide for adequate bonding.

Use of **TARGET® Polymer Bonding Agent** is recommended where concrete is smooth or whenever the possibility of a poor bond may be suspected.

FEATURES

DRYMIX PARGING MIX

- Is convenient to carry and use
- Provides consistency in quality of mix.
- Provides consistent results with the addition of colour.

MIXING INSTRUCTIONS

ALWAYS USE AN APPROVED DUST MASK WHEN LOADING MIXER WITH DRY MATERIALS.

DRYMIX PARGING MIX is complete except for **measured** amounts of clean, potable water and colour pigment. **Do not add any other ingredients.**

If a special blend is required for your purpose, contact **TARGET**.

It is important to understand that the **DRYMIX PARGING MIX** product is already thoroughly mixed. It mainly requires wetting out. For best results do not let mix become dry or tight! Allow the mix to have as much water as it requires.

FOR 6 BAG MIX

- Add 30 litres of clean potable water. Add colour pigment if required.
- Add 3 bags of **DRYMIX PARGING MIX** (120 kg)
- All DRYMIX Colour is added at the rate of one pack for two - 40 kg bags of **DRYMIX PARGING MIX**.
- Add approx 20 litres of water. Add 3 bags of **DRYMIX PARGING MIX** (120 kg)

NOTICE: Obtain the applicable **LIMITED WARRANTY** at www.targetproducts.com/product-warranty
Or send a written request to Target Products Ltd., Five Concourse Parkway, Atlanta, GA 30328, USA.
Manufactured by Target Products Ltd. ©2019 Quikrete International, Inc.



**T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D**

DRYMIX BRAND **PARGING MIX**

June 2019 Page 2 of 2

MIXING INSTRUCTIONS continued

- When all material is in mixer, mix until no dry parts is visible, about 2 minutes. At this point the mix should be slightly wetter or of higher flow than desired for spreading.
- Stop mixer for a minimum of 10 minutes. This will allow the lime to fatten and all other ingredients to absorb the water. Mix will thicken. Longer is better...lime may require up to 30 minutes to achieve optimum plasticity.
- **Restart mixer for 1 minute before adding additional water. Add additional water carefully. Mix for 1 to 2 more minutes.**
- **Excessive mixing will entrain excessive air and reduce the strength. Do not run mixer continuously.**
- Cover mixer during hot weather.
- Use mix within 1.5 hour from final mixing.

COVERAGE

Each 40 kg (88 lb) bag of **DRYMIX PARGING MIX** will cover approximately 6.5-7.5 m² (70-80 ft²) at 3 mm (1/8 inch) thickness.

SIZE

DRYMIX Parging Mix comes in 40 kg (88 lb) bags packaged 40 bags per pallet.

STORAGE

Store in a dry place. Keep out of reach of children.

CAUTION

ALWAYS USE AN APPROVED DUST MASK WHEN LOADING MIXER WITH DRY MATERIALS.

When mixed with water, the cement in this product forms a caustic solution of calcium hydroxide. Avoid contact with eyes. Avoid ingestion or inhalation. Wear appropriate clothing when working with **DRYMIX PARGING MIX** and avoid contact with skin, or with wet clothing.

First Aid Treatment: If splashed in eyes or on skin, flush thoroughly with water. Obtain Medical advice if irritation persists.

NOTICE: Obtain the applicable **LIMITED WARRANTY** at www.targetproducts.com/product-warranty
Or send a written request to Target Products Ltd., Five Concourse Parkway, Atlanta, GA 30328, USA.
Manufactured by Target Products Ltd. ©2019 Quikrete International, Inc.



T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D