



**CEMENT & CONCRETE PRODUCTS™**

# CONCRETE CRACK SEAL

PRODUCT NOS. 8640-00, -01, -15

## PRODUCT DESCRIPTION

QUIKRETE® Concrete Crack Seal is uniformly blended latex emulsion which is formulated to fill cracks in horizontal concrete surfaces.

## PRODUCT USE

QUIKRETE® Concrete Crack Seal is formulated to fill cracks on any horizontal concrete surface, including sidewalks, walkways, steps, patios, decks, appliance platforms, etc. There is nothing to add. Just shake the ready-to-use product and pour directly from the container. The product blends in with the natural gray color of concrete.

## SIZES

• QUIKRETE® Concrete Crack Seal is available in 5.5 ounce (163 ml) squeeze tubes, one quart (946 ml) and one gallon (3.8 L) plastic bottles.

## YIELD

• One quart (946 ml) bottle will fill a ¼" x ½" (6 x 12 mm) crack 38' (11.6 M) long

## INSTALLATION

### SURFACE PREPARATION

Shake well before using. Clean all loose dirt, dust and gravel from the crack. Surfaces to receive Concrete Crack Seal should be free of oil and grease. Cleaning with QUIKRETE® Concrete & Asphalt Cleaner (#8601) is recommended to insure the best bond. If the crack is deeper than ¼" (6 mm), use backer rod or sand to fill the crack to within ¼" (6 mm) of the surface.

### APPLICATION

Cut the tip of the spout to make a ¼" (6 mm) to 3/8" (9 mm) hole. Squeeze Concrete Crack Seal into the crack, over-filling slightly to allow for shrinkage. A second coat can be applied after 24 hours as needed to provide a uniform finished surface.

## DIVISION 3

Concrete Materials &  
Methods 03 05 00



## PRECAUTIONS

• Do not apply in cracks wider than ½" (12 mm). Temperature should be between 45°F and 100°F (7°C and 38°C). Keep product from freezing. Do not apply if rain is expected within 24 hours. Do not apply to surfaces which will later be coated with anything other than acrylic water-based paint.

## WARRANTY

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing. This limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies  
One Securities Centre  
3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305  
(404) 634-9100 • Fax: (404) 842-1425