GLASS BLOCK MORTAR MIX (WHITE)

July, 19 Page 1 of 2

PRODUCT

TARGET[®] White Glass Block Mortar Mix is an accurate blend of white Portland cement, specially graded white aggregates and admixtures to give increased ease of installation and improved water resistance. The product is designed for use in the installation of glass blocks, but is also suitable for other applications where a white mortar is required. The use of this premixed mortar eliminates the variability problems caused by site batching and guarantees a quality material with improved water resistance.



USES

TARGET White Glass Block Mortar Mix can be used to set and grout all types of glass blocks. It also can be used to repoint or repair existing mortar joints that have been damaged, or for any application requiring a white Portland cement mortar.

PROCEDURES

- 1. Ensure framing is of proper dimension and free of all contaminants and loose materials. Glass blocks should also be clean.
- 2. Install asphalt emulsion and expansion strips to manufacturer's specifications.
- Mix mortar thoroughly with clean water to a stiff consistency. Use 4 4.8 L of clean water per 50 lb (22.7 kg) bag
- 4. Allow material to stand for approximately 5 minutes, then remix before use.
- 5. Place a full bed of mortar on the base or sill. Do not furrow. Set lower course of glass block and tap into place using wooden or rubber mallet. Set each course of glass block in a full bed of mortar. Smooth out joints at initial set.
- 6. Anchors and reinforcing to be placed to manufacturer's specifications.
- 7. Tool joints smooth and concave before mortar takes final set.
- Excess mortar must be removed from glass block facing before mortar hardens. A stiff bristle brush and damp cloth are preferable for removing the excess mortar.

CAUTION

TARGET White Glass Block Mortar Mix should not be placed where temperatures are below 10 $^{\circ}$ C (50 $^{\circ}$ F) or above 29 $^{\circ}$ C (85 $^{\circ}$ F) during or for the first 24 hours after installation.

YIELD

Each bag weighs 22.7 kg (50 lb).

Typical quantities required for standard installations are:

6 inch glass block	9.29 m ² (100 ft ²)	10 bags
8 inch glass block	9.29 m ² (100 ft ²)	7 bags
12 inch glass block	9.29 m² (100 ft²)	5 bags

NOTICE: Obtain the applicable **LIMITED WARRANTY** at www.targetproducts.com/product-warranty Or send a written request to Target Products Ltd., Five Concourse Parkway, Atlanta, GA 30328, USA. (B) Quikrete Canada Holdings, Limited. Manufactured by Target Products Ltd. ©2019 Quikrete International, Inc.



GLASS BLOCK MORTAR MIX (WHITE)

July, 19 Page 2 of 2

PACKAGING

TARGET White Glass Block Mortar Mix – Stock Code 9991192 - is available in 25 kg (55 lb) bag 56 bags /pallet.



NOTICE: Obtain the applicable **LIMITED WARRANTY** at www.targetproducts.com/product-warranty Or send a written request to Target Products Ltd., Five Concourse Parkway, Atlanta, GA 30328, USA. (a) Quikrete Canada Holdings, Limited. Manufactured by Target Products Ltd. (c) 2019 Quikrete International, Inc.