# INDUSTRIAL SANDS - AB

May, 2020 Page 1 of 2

### **PRODUCT**

TARGET® Industrial Sands are well-graded processed sands mined from natural sand deposits in Alberta. They are available in the following standard grades:

Grade	Typical Particle Size Range	
Bedding Sand	6 mm minus	
Specialty Sand	As per customer specification	
Agricultural Sand	Available on request	

## **USES AND ADVANTAGES**

TARGET Industrial Sands are suitable for use in ferro-cement work, polymer mortars or concretes and other applications requiring well-graded fillers or aggregates.

### PHYSICAL PROPERTIES

Colour Tan

Grain Shape Sub-rounded

Bulk Density 95 - 100 lb/ft<sup>3</sup> (1,520 - 1,600 kg/m<sup>3</sup>)

Hardness, Mohs 6.5 - 7 Specific Gravity 2.65

Moisture Content <0.1% weight Acid Solubility <5% weight

Bulk density values vary with particle size. Values for individual products can be determined at the time of shipping if required.

# TYPICAL CHEMICAL ANALYSIS and PROPERTIES

Chemical Compound		Typical Value, % weight
Silica	SiO <sub>2</sub>	93 - 95.5 %
Alumina	Al <sub>2</sub> O <sub>3</sub>	3.0 - 4.5 %
Iron Oxide	Fe <sub>2</sub> O <sub>3</sub>	0.25 - 0.35 %
Calcium Oxide	CaO	0.25 - 0.65 %
Magnesium Oxide	MgO	0.07 - 0.15 %
Sodium Oxide	Na₂O	0.60 - 0.80 %
Titanium Oxide	TiO <sub>2</sub>	0.10 max
Loss on Ignition	LOI	0.30 - 0.55 %



# RGET PRODUCTS

# INDUSTRIAL SANDS - AB

May, 2020 Page 2 of 2

# **PACKAGING - INDUSTRIAL OR SPECIALTY**

TARGET Industrial sands are available via bulk deliveries and can be packaged in 1.75 tonne bulk bags and 25 kg (50 lb) plastic bags on request.

