

TARGET PRIMER

June, 2019 Page 1 of 1

PRODUCT

TARGET® Primer is an aqueous emulsion of a polymer and chemical admixtures. It is designed for use as a floor sealer and primer in conjunction with TARGET Floor Leveller C26 UL.

TARGET Primer is intended only for use as a sealer and primer for surfaces to which TARGET Floor Leveller C26 UL are to be applied.

APPEARANCE

White, milky liquid

PROCEDURES

1. Prepare existing concrete or sub-floor surfaces by removing all traces of dirt, dust, oil, grease, efflorescence, laitance and loose or deteriorated material. Sweep, vacuum clean, or use air jets to remove all loose material. In most cases mechanical roughening of concrete by shotblasting, sandblasting or high pressure water blasting is desirable. Do not acid etch.
2. The primer is mixed with clean water before application at a ratio of 1 part of TARGET Primer to 3 parts water by volume.
3. Apply the primer mixture to the floor by brush or roller (do not spray) before placing TARGET Floor Leveller C26 UL. Additional brushing or rolling of the applied primer is required to ensure adequate sealing if any dust is present on the floor. Allow the primer to become surface-dry before applying the levelling material. A drying time of not less than two hours is usually required. On porous or highly absorbent surfaces, two coats of primer mixture should be applied to ensure sealing of voids. Allow a drying time of 1 to 2 hours between coats.
4. Formation of pools of primer should be avoided if possible. Any pools should be removed by spreading out with a brush prior to setting.

TEMPERATURE

The concrete or sub-floor and air temperatures should be kept above 5 °C (41 °F) during application of TARGET Primer.

CAUTION

- DO NOT allow TARGET Primer to freeze.
- DO NOT place TARGET Floor Leveller C26 UL over pools of TARGET Primer. The primer should be applied uniformly to achieve the required degree of penetration and sealing.

COVERAGE

At the specified dilution ratio, the approximate coverage obtained from concentrated TARGET Primer is 14 m² per liter (570 ft² per US gallon) per coat for most surfaces.

PACKAGING

TARGET Primer is available in 3.8 L (1 US gal) pails.



NOTICE: Obtain the applicable **LIMITED WARRANTY** at www.targetproducts.com/product-warranty
Or send a written request to Target Products Ltd., Five Concourse Parkway, Atlanta, GA 30328, USA.
© Quikrete Canada Holdings, Limited. Manufactured by Target Products Ltd. ©2019 Quikrete International, Inc.

T
A
R
G
E
T

P
R
O
D
U
C
T
S

L
T
D