PRO-GRIT

April, 2024 Page 1 of 2

PRODUCT

PRO-GRIT® holds a solid place in the North American market because of its unparalleled quality.

USES AND ADVANTAGES

Recommended for cleaning rust, paint or scale on steel

FEATURES

- Best performing product in its category
- Low dust emission
- Clean faster requiring less product
- Contains less than 0.1% free silica
- Compliant with SSPC-AB1 and MIL-A-22262B (SH) standards

PHYSICAL PROPERTIES

Particle shape: Angular

Color: Black


Hardness: 7.0 - 7.5 MOHS Density: 112 lb/ft³ - 1794 kg/m³

Specific gravity: 3.5

Specific granulometries available on demand









12-40

20-40

30-60

36-70



PRO-GRIT

April 2024 Page 2 of 2

TYPICAL CHEMICAL ANALYSIS

Ingredient Name	%	CAS Number
Iron oxide (FE2O3)	50-60	1309-37-1
Silicon Dioxide Amorphous silica	30-40	7631-86-9
Calcium oxide	1-10	1305-78-8
Aluminum oxide	0-5	1344-28-1
Zinc	0-2	7440-66-6
Copper	0-0.8	7440-50-8

SIEVE ANALYSIS

Sieves (AST	M E11)	% retained	6 retained				
US Mesh	mm	#1240	#2040	#3060	#3570		
6	3.350	0.0	0.0	-	-		
8	2.360	0.7	0.7	-	-		
12	1.700	-	13.0	-	-		
14	1.400	13.0	14.0	0.0	-		
16	1.180	-	27.0	3.8	-		
18	1.000	-	-	13.2	-		
20	0.850	14.0	13.2	18.7	0.0		
30	0.600	-	ı	29.7	1.0		
35	0.500	27.0	29.7	-	18.8		
40	0.425	-	ı	17.7	20.8		
50	0.300	-	ı	-	26.4		
70	0.212	13.2	2.4	12.3	15.3		
100	0.150	-	ı	2.3	9.0		
140	0.106	-	-	-	5.9		
200	0.075	-	-	-	2.1		
PAN		29.7	0.0	2.4	0.8		

PACKAGING

9992471 Pro-grit 20/40 & 30/601814 kg (4000 lb) bulk bag, 1 per pallet Also available in 22.6 kg (50 lb) bags 63 bags per pallet

