## **Target Products**



# SAFETY DATA SHEET

SECTION I - PRODUCT AND SUPPLIER INFORMATION

Supplier:

Target Products Ltd, 1080 Bradner Road Abbotsford, BC V4X 1H8 Telephone: 1.604.856.7976

24-Hour Emergency Response Telephone for Transport Emergencies ONLY: +1 (613) 996-6666

#### PRODUCT

4300 PSI Concrete Mix Anti Washout Grout Aquaplug Concrete 30 MPa Concrete 35 MPa **Concrete Resurfacer CT Patch** Fast Set Patching Concrete Floor Finish Patch Floor Hardener – Non Metallic Floor Hardener – Synthetic Floor Leveller C26 UL Flowcrete **Machine Base Grout** Match Patch Pipe Patch Plain Shotcrete **Portland Expanding Grout** Sacking Mix SC-100. D and W Speedset Stack and Bank TRAFFIC PATCH<sup>™</sup>, Coarse and Fine Trowelable Stamp Mix V/O Repair Mortar Vetonit Plaano SL Plus

#### SDS Identifier: Concrete Related, Series 1

Product Use: Portland cement based repair materials

#### SECTION II - HAZARD IDENTIFICATION

Hazard-determining components of labeling: Silica, Portland cement 2.1 Classification of the substance or mixture Carcinogen – Category 1A Skin Corrosion – Category 1B Eye Corrosion – Category 1B Skin Sensitization – Category 1B Specific Target Organ Toxicity Repeat Exposure – Category 1 Specific Target Organ Toxicity: Single Exposure – Category 3

#### 2.2a Signal word DANGER!

#### 2.2b Hazard Statements

May cause cancer through chronic inhalation Causes severe skin burns and serious eye damage

## **Target Products**

May cause an allergic skin reaction Causes damage to lungs through prolonged or repeated inhalation May cause respiratory irritation





2.2d Precautionary statements
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear impervious gloves, such as nitrile. Wear eye protection, and protective clothing.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Use only in a well-ventilated area.
Do not breathe dust.

If swallowed: Rinse mouth. Do NOT induce vomiting.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If on skin (or hair): Remove immediately all contaminated clothing and wash before re-use. Rinse skin or hair with water.
If significant skin irritation or rash occurs: get medical advice or attention.

#### Immediately seek medical advice or attention if symptoms are significant or persist.

Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/containers in accordance with all regulations.

#### 2.3 Additional

The Portland cement in this product can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns.

Burns from Portland cement may not cause immediate pain or discomfort. You cannot rely on pain to alert you to cement burns. Therefore precautions must be taken to prevent all contact with Portland cement. Cement burns can become worse even after contact has ended. If there is contact with this product, immediately remove all product from body and thoroughly rinse with water. If you experience or suspect a cement burn or inflammation you should immediately see a health care professional.

Skin burns and irritation may be caused by brief exposure, though often are caused by extended exposure of 15 minutes, an hour, or longer. Interaction of Portland cement with water or sweat releases a caustic solution which produces the burns or irritation. Any extended exposure should be treated as though a burn has occurred until determined otherwise.

Skin contact with Portland cement can also cause inflammation of the skin, referred to as dermatitis. Signs and symptoms of dermatitis can include itching, redness, swelling, blisters, scaling, and other changes in the normal condition of the skin. Signs and symptoms of burns include the above and whitening, yellowing, blackening, peeling or cracking of skin.

The Portland cement in this product may cause allergic contact dermatitis in sensitized individuals. This overreaction of the immune system can lead to severe inflammation. Sensitization may result from a single exposure to the low levels of Cr(VI) in Portland cement or repeated exposures over months or years. Sensitization is long lasting and, after sensitization, even very small quantities can trigger the dermatitis. Sensitization is uncommon. Individuals, who experience skin problems, including seemingly minor ones, are advised to seek medical attention.

#### 2.3a HNOC - Hazards not otherwise classified: Not applicable

#### 2.3b Unknown Acute Toxicity: None

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION			
Hazardous Components	CAS No.	<u>% by Weight</u>	
Sand, Silica, Quartz	14808-60-7	60-100*	
Portland Cement	65997-15-1	30-60*	

\*The concentrations ranges are provided due to batch-to-batch variability.

4.1	Description of the	first-aid measures
Gei	neral information:	

After inhalation: Remove person to fresh air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration. In case of unconsciousness, place patient stably in side position for transportation.

After skin contact: Wash skin with cool water and pH-neutral soap or a mild detergent. If significant skin irritation or rash occurs: get medical advice or attention.

After eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. After swallowing: Do not induce vomiting. If conscious, have the victim drink plenty of water and call a physician immediately. Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms/effects, acute and delayed

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated inhalation. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

Skin contact: The Portland cement in this product can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns.

Burns from Portland cement may not cause immediate pain or discomfort. You cannot rely on pain to alert you to cement burns. Therefore precautions must be taken to prevent all contact with Portland cement. Cement burns can become worse even after contact has ended. If there is contact with this product, immediately remove all product from body and thoroughly rinse with water. If you experience or suspect a cement burn or inflammation you should immediately see a health care professional.

Skin burns and irritation may be caused by brief exposure, though often are caused by extended exposure of 15 minutes, an hour, or longer. Interaction of Portland cement with water or sweat releases a caustic solution which produces the burns or irritation. Any extended exposure should be treated as though a burn has occurred until determined otherwise.

Skin contact with Portland cement can also cause inflammation of the skin, referred to as dermatitis. Signs and symptoms of dermatitis can include itching, redness, swelling, blisters, scaling, and other changes in the normal condition of the skin. Signs and symptoms of burns include the above and whitening, yellowing, blackening, peeling or cracking of skin.

The Portland cement in this product may cause allergic contact dermatitis in sensitized individuals. This overreaction of the immune system can lead to severe inflammation. Sensitization may result from a single exposure to the low levels of Cr (VI) in Portland cement or repeated exposures over months or years. Sensitization is long lasting and, after sensitization, even very small quantities can trigger the dermatitis. Sensitization is uncommon. Individuals, who experience skin problems, including seemingly minor ones, are advised to seek medical attention.

**Eye Contact:** Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

#### 4.3 Indication of immediate medical attention and special treatment needed:

Immediately seek medical advice or attention if symptoms are significant or persist.

## SECTION V - FIRE FIGHTING MEASURES

5.1 Flammability of the Product: Non-flammable and non-combustible

- 5.2 Suitable extinguishing agents: Treat for surrounding material
- 5.3 Special hazards arising from the substance or mixture: None

5.3a Products of Combustion: None

5.3b Explosion Hazards in Presence of Various Substances: Non-explosive in presence of shocks

## SECTION VI – ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Wear personal protective equipment (See section VIII). Keep unprotected persons away.

#### 6.2 Methods and material for containment and cleaning up:

Do not allow to enter sewers/ surface or ground water. Dispose of unwanted materials and containers properly in accordance with all regulations.

#### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

## 7.1 Handling

**Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace. DO NOT BREATHE DUST. In dusty environments, the use of an OSHA, MSHA or NIOSH approved respirator and tight fitting goggles is recommended. Wear appropriate PPE (See section 8).Do not mix with other chemical products, except as indicated by the manufacturer. Do not get in eyes, on skin or clothing. Good housekeeping is important to prevent accumulation of dust.

#### 7.2 Storage

Requirements to be met by storerooms and receptacles: No special requirements. Information about storage in one common storage facility: Not required.

**Further information about storage conditions:** Keep out of the reach of children. Keep container tightly closed and prevent exposure to humidity. Do not allow water to contact the product until time of use to preserve product utility.

SECTION VIII – EXPOSURE CONTROL MEASURES / PERSONAL PROTECTION					
8.1 Components with limit values that require monitoring at the workplace:					
Hazardous Components	CAS No.	PEL (OSHA) mg/M <sup>3</sup>	TLV (ACGIH) mg/M³		
Silica Sand, crystalline Portland Cement	14808-60-7 65997-15-1	0.1 5 (resp) 15 (total)	0.025 (resp) 10 (resp)		

#### 8.2 Exposure Controls

Use ventilation adequate to keep exposures below recommended exposure limits.

#### 8.3 General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

#### 8.3a Personal protective equipment

#### Protection of hands:

Wear gloves of adequate length to offer appropriate skin protection from splashes. Nitrile, Butyl and PVC gloves have been found to offer adequate protection for incidental contact. Precautions must be observed because burns occur with little warning -- little heat is sensed.

#### Eye protection:

Wear approved eye protection (properly fitted dust- or splash-proof chemical safety glasses.

#### Respiratory protection:

A NIOSH-approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional, following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

#### SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

General Information	
Appearance	Form: Granular Solid
	Color: Gray to gray-brown colored
	Odor: None
pH-value at 20°C (68 °F):	13 (10%)
Boiling point/Boiling range:	Not applicable
Flash point:	Not applicable
Auto igniting:	Product is not self-igniting
Vapor pressure at 21°C (70°F)	Not available
Density at 25°C (77 °F):	2.6 to 3.15
Solubility in / Miscibility with	
Water:	Insoluble
VOC content:	0 g/L VOC

#### SECTION X - STABILITY AND REACTIVITY

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal storage conditions. Keep in dry storage.

10.3 Possibility of hazardous reaction

No dangerous reaction known under conditions of normal use.

10.4 Thermal decomposition / conditions to be avoided

No decomposition if used according to specifications.

10.5 Incompatible materials

Contact of silica with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, or oxygen difluoride may cause fires

10.6 Hazardous Decomposition or By-products

Silica will dissolve in Hydrofluoric Acid and produce a corrosive gas - silicon tetrafluoride.

#### SECTION XI - TOXICOLOGICAL INFORMATION

11.1 Exposure Routes: Skin contact, skin adsorption, eye contact, inhalation, or ingestion.

#### 11.2 Symptoms related to physical/chemical/toxicological characteristics:

## **Target Products**

**Inhalation:** May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

**Skin contact:** Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact. Product becomes extremely alkaline when exposed to moisture, and can cause alkali burns and affect the mucous membranes.

**Eye Contact:** Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Ingestion: Harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

## 11.3 Delayed, immediate and chronic effects of short-term and long-term exposure Short Term

	Skin Corrosion/Irritation: Causes severe skin burns.
	Serious Eye Damage/Irritation: Causes severe eye damage.
	Respiratory Sensitization: Not available
	Skin Sensitization: May cause an allergic skin reaction.
	Specific Target Organ Toxicity-Single Exposure: (Category 3) May cause respiratory irritation.
	Aspiration Hazard: Not available
Long Ter	m .
-	Carcinogenicity: May cause cancer through chronic inhalation.
	Germ Cell Mutagenicity: Not available
	Reproductive Toxicity: Not available
	Specific Target Organ Toxicity- Repeated Exposure: (Category 1) Causes damage to lungs through prolonged/repeated exposure

Synergistic/Antagonistic Effects: Not available.

#### SECTION XII - ECOLOGICAL INFORMATION

#### 12.1 Ecotoxicity

May cause long-term adverse effects to the aquatic environment. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or un-neutralized

#### 12.2 Persistence and degradability

No further relevant information available.

#### 12.3 Bioaccumulative potential:

No further relevant information available.

#### 12.4 Mobility in soil

No further relevant information available.

#### 12.5 Other Adverse Effects

No further relevant information available.

#### SECTION XIII - DISPOSAL CONSIDERATIONS

#### 13.1 Waste Disposal Method

The packaging and material may be land filled; however, material should be covered to minimize generation of airborne dust. This product is <u>not</u> classified as a hazardous waste under the authority of the RCRA (40CFR 261) or CERCLA (40CFR 117&302). Disposal must be made in accordance with local, state and federal regulations.

## 13.2 Other disposal considerations

#### Uncleaned packaging

**Recommendation:** Disposal must be made in accordance with local, state and federal regulations. **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## SECTION XIV – TRANSPORT INFORMATION

UN-Number UN proper shipping name Transport Hazard Class(es) Packing Group (if applicable) DOT (U.S.) Not Regulated Not Regulated Not Regulated Not Regulated TDG (Canada) Not Regulated Not Regulated Not Regulated Not Regulated

## 14.1 Environmental hazards:

Not Available

**14.2 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code** Not available

## 14.3 Special precautions for user

Do not handle until all safety precautions have been read and understood.

#### SECTION XV - OTHER REGULATORY INFORMATION

#### 15.1 Safety, Health and Environmental Regulations/Legislations specific for the chemical

#### Canada

WHMIS Classification: Considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and subject to the requirements of Health Canada's Workplace Hazardous Material Information (WHMIS). This document complies with the WHMIS requirements of the Hazardous Products Act (HPA) and the CPR.

#### 15.2 US Federal Information

#### SARA 302/311/312/313 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302, 311, 312 or 313.

RCRA: Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 et seq.

CERCLA: Crystalline silica (quartz) is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR §302.

Emergency Planning and Community Right to Know Act (SARA Title III): Crystalline silica (quartz) is not an extremely hazardous substance under Section 302 and is not a toxic chemical subject to the requirements of Section 313.

FDA: Silica is included in the list of substances that may be included in coatings used in food contact surfaces, 21 CFR §175.300(b)(3)(xxvi).

NTP: Respirable crystalline silica, primarily quartz dusts occurring in industrial and occupational settings, is classified as Known to be a Human Carcinogen.

OSHA Carcinogen: Crystalline silica (quartz) is not listed.

#### 15.4 Global Inventories

DSL All components of this product are on the Canadian DSL list.

TSCA No.: Crystalline silica (quartz) appears on the EPA TSCA inventory under the CAS No. 14808-60-7. All constituents are listed in the TSCA inventory.

#### SECTION XVI - OTHER INFORMATION

## Last Updated: June 19, 2024

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by Target Products, Ltd. - Phone 1.604.856.7976

www.TargetProducts.com End of SDS