


*Concrete Products*



*Concrete Repair*



*Masonry Products*



*Your partner in quality • For all your concrete needs*



# Fast Setting Concrete No Mixing Required



## TABLE OF CONTENTS

ITEM #	PRODUCT	PAGE
<b>CONCRETE PRODUCTS</b>		
110125	CONCRETE MIX • 25 kg bag .....	1
100465	POSTHASTE® CONCRETE MIX • 25 kg bag.....	1
100425	QUIKRETE® FAST SETTING CONCRETE • 25 kg bag .....	2
100725	QUIKRETE® 6000 • 25 kg bag.....	2
110682	COUNTERTOP MIX • 36.3 kg bag .....	3
110326	SAND / TOPPING MIX • 25 kg bag .....	3
158556	PORTLAND EXPANDING GROUT • 22.7 kg bag .....	4
124152	COMMERCIAL GRADE FASTSET™ Mortar Repair - 22 kg.....	4
158553	COMMERCIAL GRADE FASTSET™ All-Crete™ - 22 kg .....	5
<b>MASONRY PRODUCTS</b>		
113655	MASON MIX (TYPE S MORTAR) • 25 kg bag.....	5
115525	WATER RESISTANT PARGING MIX • 25 kg bag.....	6
123151	QUIKWALL SURFACE BONDING CEMENT – GRAY • 22.7 kg bag.....	6
<b>CEMENTS AND LIME</b>		
112425, 405942	GU (TYPE 10) CEMENT • 40 kg bag, 20 kg bag.....	7
112525	MCS (MORTAR S) CEMENT • 34 kg bag.....	7
112479	HE (TYPE 30) PORTLAND CEMENT • 40 kg bag .....	8
9994022	HS (TYPE 50) PORTLAND CEMENT • 20 kg bag, 40 kg bag .....	8
9994010	WHITE PORTLAND CEMENT   FEDERAL WHITE • 40 kg bag .....	8
405951	PORTLAND CEMENT LIME BLEND • 30 kg bag.....	9
9994028	HYDRATED LIME – TYPE 'S' • 23 kg bag.....	9
9994035	HYDRATED LIME – TYPE 'N' • 22.68 kg bag .....	9
<b>REPAIR PRODUCTS - BAGS</b>		
113318	BONDED TOPPING MIX • 18 kg bag.....	10
113147	ReCap™ RESURFACER • 18 kg bag.....	10
124958	FAST-SET SELF-LEVELING FLOOR RESURFACER • 22 kg .....	11
170125	BLACK TOP PATCH • 25 kg bag .....	11
<b>HARDSCAPES - SANDS AND AGGREGATE PRODUCTS</b>		
111325	PREMIUM PLAY SAND • 25 kg bag.....	12
115125	ALL PURPOSE GRAVEL • 25 kg bag.....	12
115155	BASE ROCK • 25 kg bag.....	13
115036	PATIO PAVER JOINTING SAND • 36 kg bag .....	13
115831	TRACTION SAND • 18 kg bag .....	13
99933050	SILICA ABRASIVE 30-50 • 22.7 kg bag.....	14
116036	1/4 DOWN – LIMESTONE • 25 kg bag.....	14



## TABLE OF CONTENTS

ITEM #	PRODUCT	PAGE
<b>HARDSCAPES - EARTH ESSENTIALS</b>		
137550	PLAY SAND EARTH ESSENTIALS • 18 kg bag.....	15
127558	POLYMERIC JOINTING SAND EARTH ESSENTIALS • 18 kg bag.....	15
137546	LIMESTONE SCREENINGS EARTH ESSENTIALS • 18 kg bag.....	15
137530	RED CRUSHED TILE EARTH ESSENTIALS • 18 kg bag .....	15
137504	WHITE ROCK EARTH ESSENTIALS • 18 kg bag .....	15
137517	BEACH PEBBLES EARTH ESSENTIALS • 18 kg bag.....	15
137510	PEA GRAVEL EARTH ESSENTIALS • 18 kg bag .....	15
137520	DRAINAGE GRAVEL EARTH ESSENTIALS • 18 kg bag .....	15
<b>MISCELLANEOUS PRODUCTS</b>		
692316, 692251, 2, 3	QUIK-TUBE® BUILDING FORMS • 6" x 8', 8" x 8', 10" x 8', 12" x 8' EA.....	15
692132	WALK MAKER® BUILDING FORM • 2' x 2' X 2" EA.....	15
131720, 1, 2, 3	LIQUID CEMENT COLOUR • 296 ml bottle .....	16
691741	BACKER ROD • 3/4" dia x 20' EA.....	16
691706	EXPANSION JOINT STRIPS • 5'-0" long EA.....	17
861016	ACRYLIC FORTIFIER • 0.95 L bottle .....	17
860112	CONCRETE & ASPHALT CLEANER - CONCENTRATE • 946 ml bottle .....	18
873102	ACRYLIC CONCRETE CURE & SEAL (SATIN) • 3.8 L.....	18
<b>REPAIR PRODUCTS – PATCHING PRODUCTS</b>		
113304	BONDED TOPPING MIX • 4.5 kg pail .....	19
112612, 112606	HYDRAULIC WATER STOP CEMENT • 4.5 kg, 9 kg.....	19
124512	ANCHORING CEMENT • 4.5 kg pail.....	20
124012	QUICK-SETTING CEMENT • 4.5 kg pail.....	20
990203, 990216	CONCRETE BONDING ADHESIVE • 3.8 L, 0.95 L bottle .....	21
865036	CONCRETE PATCHING COMPOUND • 946 ml pail.....	21
124116	ZIP AND MIX REPAIR MORTAR • 1.35 kg bag .....	22
865033	PRE-MIXED STUCCO PATCH • 0.95 L pail .....	22
120145	EXTERIOR STUCCO PATCH • 4.5 kg pail.....	22
<b>REPAIR PRODUCTS – JOINT AND CRACK REPAIR</b>		
864002	GREY CONCRETE CRACK SEALER • 946 ml bottle.....	23
862012	CONCRETE REPAIR • 296 ml tube .....	23
865011	STUCCO CRACK REPAIR • 296 ml tube.....	24
862002	MORTAR REPAIR • 296 ml tube .....	24
862025	FIREPLACE MORTAR • 296 ml tube .....	25
862019	POLYURETHANE MORTAR JOINT SEALANT • 296 ml tube.....	25
866012, 866032	POLYURETHANE SEALANT GRAY – SELF LEVELLING • 300 ml, 858 ml tube .....	26
866013	POLYURETHANE SEALANT – NON-SAG • 296 ml tube .....	26
862032	FASTSET™ ANCHORING EPOXY • 254 ml tube.....	27
990212, 990213	COMMERCIAL GRADE POLYURETHANE ADHESIVE • 300 ml, 858 ml tube.....	27
<b>WATERPROOFING PRODUCTS</b>		
9991060, 59, 58	XYPEX HIGH 'N DRY • 11 kg, 5 kg, 2.27 kg pail.....	28
9991062, 9991063	XYPEX PATCH 'N PLUG • 2.27 kg, 9 kg pail .....	28

Data/Spec sheets and Safety Data Sheets (SDS) are available online

<http://www.targetproducts.com/prod-category.aspx>

# CONCRETE PRODUCTS

## CONCRETE MIX



For general concrete construction and repair of concrete where thickness in excess of 2" is required.

### Used for:

- Driveways
- Patios
- Retaining walls
- Footings
- Setting posts
- Sidewalks
- Foundations

### Features:

- Consists of cement, sands and coarse aggregates pre-mixed for quality and convenience.
- Approx. 4000 psi (27.6 MPa) in 28 days
- Sets in approximately 4 hours at 20° C (68° F)

**Mfr. No. 110125**

**Ship Weight 25 kg bag | 56 bags/pallet**

### COVERAGE

# 25kg Bags required at 4 inch thickness

AREA	1ft	2ft	3ft	4ft
1ft	1	2	3	3
2ft	2	3	5	6
3ft	3	5	7	9
4ft	3	6	9	12
5ft	4	8	12	15
1 x 25kg bag = 0.43 ft <sup>3</sup>				

SONOTUBE	6" diameter	8" diameter	10" diameter	12" diameter
Bags required per 4ft length	1.8	3	5	7.3

## POSTHASTE® CONCRETE MIX



A fast setting concrete.

### Used for:

- Setting posts
- Signs
- Footings
- Other concrete applications

### Features:

- Sets in 20 minutes.
- Eliminates; bracing, construction delays, rain washouts and unwanted depressions
- Approx. 2500 psi (17.2 MPa) in 28 days

**Mfr. No. 100465**

**Ship Wt. 25 kg bag | 56 bags/pallet**

### COVERAGE

SETTING POSTS (# of bags per hole)

Depth of Hole in Inches (Metres)	19 (.46)	24 (.61)	30 (.76)	36 (.91)	42 (1.07)	48 (1.22)
Post 3" (75mm) Hole Dia. 9" (230mm)	2	2	3	3	4	4
Post 4" (100mm) Hole Dia. 9" (300mm)	2	2	3	3	4	4
1 x 25 kg bag = 0.47 ft <sup>3</sup>						

## QUIKRETE® FAST SETTING CONCRETE



### COVERAGE

#### SETTING POSTS (# of 25kg (55lb) bags per hole)

Depth of Hole (Inches)	19 (.46)	24 (.61)	30 (.76)	36 (.91)	42 (1.07)	48 (1.22)
Post 3"	2	2	3	3	4	4
Post 4"	2	2	3	3	4	4

#### SLABS

Square Feet	2 (0.2)	5 (0.5)	10 (0.9)	25 (2.3)	50 (4.7)	100 (9.3)
4" (100mm) Thick	2	4	8	20	40	79
6" (150mm) Thick	3	6	12	30	60	118

All yields are approximate and do not allow for waste or uneven sub-grade, etc. | 1 x 25 kg bag = 0.44 ft³

A fast setting concrete with fast strength gain.

#### Used for:

- Setting posts
- Signs
- Slabs
- Footings

#### Features:

- Set posts without mixing
- Sets hard in 20-40 minutes
- Walk on it in 2 hours
- 1000 psi in 24 hours
- Approx. 4000 psi (27.6 MPa) in 28 days

**Mfr. No. 100425**

**Ship Wt. 25 kg bag | 56 bags/pallet**

## QUIKRETE® 6000



### COVERAGE

#### # 25kg Bags required at 4 inch thickness

AREA	1ft	2ft	3ft	4ft
1ft	0.75	1.5	2.3	3.0
2ft	1.5	3.0	4.6	6.1
3ft	2.3	4.6	6.9	9.2
4ft	3.0	6.1	9.2	12.3
5ft	3.8	7.7	11.5	15.3

Construction and repair of concrete where extra strength is required.

#### Used for:

- Slabs
- Steps
- Patios
- Deck support
- Curbs, Patching existing concrete
- Driveways

#### Features:

- High strength concrete (6000 psi) (41 MPa ) in 28 days.
- Fast strength gain (1 day = 2000 psi).
- Walk on in 8 hours.
- Allows construction in 24 hours
- Withstands higher impact and wears longer than regular concrete
- Less shrinkage

**Mfr. No. 100725**

**Ship Wt. 25 kg bag | 56 bags/pallet**

## COUNTERTOP MIX



### COVERAGE

# of 36.3 kg bags required

Square Feet (M2)	6 (0.56)	10 (0.93)	25 (2.32)	50 (4.65)
1.5" Thick (37mm) # of 36.3 kg (80lb)	2	3	6	11
2" Thick (50mm) # of 36.3 kg (80lb)	2	3	7	14
3" Thick (75mm) # of 36.3 kg (80lb)	3	5	11	21

Countertop Mix is a flowable, high strength commercial grade concrete mix designed for use in concrete countertops, requiring only the addition of water.

#### Used for:

- Countertop Mix is designed specifically for casting concrete countertops.

#### Features:

- Super-plasticizer additive provides a flowable mix at the low water / cement ratio.
- High-flow formula minimizes the need for mechanical vibration.
- Reduced-shrinkage formulation.
- Approx 5000 psi (34.5 MPa) in 28 days.

**Mfr. No. 110682**

**Ship Wt. 36.3 kg bag | 42 bags/pallet**

## SAND / TOPPING MIX



### COVERAGE

# of bags required for 1" or 2" topping

Square Feet (M2)	5 (0.5)	10 (0.9)	20 (1.9)	35 (3.3)	50 (4.7)
1" Thick (25 mm) # of 25 kg (55lb)	1	2	4	7	10
2" Thick (50mm) # of 25 kg (55lb)	2	4	8	14	20

Patching or resurfacing damaged concrete where up to 2" thickness is required.

#### Used for:

- Driveways, Patios, Sidewalks etc.
- A base for laying flagstone & pavers
- Shower base

#### Features:

- Consists of cement, fine and coarse sand and admixtures.
- Approx. 4000 psi (27.6 MPa) in 28 days
- Just add water
- Concrete bonding adhesive is required to ensure proper bonding of overlay

**Mfr. No. 110326**

**Ship Wt. 25 kg bag | 56 bags/pallet**

## PORTLAND EXPANDING GROUT



A high-strength non-shrink grout used for the following applications.

### Used for:

- Grouting under columns and base plates
- Anchoring of posts and bolts into concrete
- Filling voids and cracks
- Repair to concrete structures

### Features:

- High strength – up to 8800 psi (60.5 MPa)
- 3200 psi (22 MPa) in 24 hours
- Non-shrink
- Up to 6" in thickness

**Mfr. No. 158556**

**Ship Wt. 22.7 kg bag | 56 bags/pallet**

### COVERAGE

No of 22.7 kg bags required for 1" or 2" topping

Square Feet (M2)	5 (0.5)	10 (0.9)	20 (1.9)	35 (3.3)	50 (4.7)
1" Thick (25mm) # of 25 kg (55lb)	1	2	4	7	10
2" Thick (50mm) # of 25 kg (55lb)	2	4	8	14	20

## COMMERCIAL GRADE FASTSET™ MORTAR REPAIR



QUIKRETE FastSet Repair Mortar is a rapid setting structural mortar for repairing all concrete surfaces including vertical and overhead applications.

### Uses:

- Walls
- Bridges
- Tunnels
- Sewers, culverts
- Columns

### Features:

- Superior bonding
- Sets in 20 minutes
- High strength 2000 PSI (13.8 Mpa) in 3 hours
- 6000 PSI (41.4 MPa) in 28 days

**Mfr. No. 124152**

**Ship Wt. 22.7 kg bag | 30 bags/pallet**

### COVERAGE

No of 22.7 kg (50 lb) bags

Thickness	2 (0.2)	5 (0.5)	10 (0.9)	15 (1.4)	20 (1.8)	50 (4.6)
1" (25mm)	1	1	2	3	4	9
2" (50mm)	1	2	4	5	6	17
*3 (75mm)	1	2	4	6	8	10
4 (100mm)	1	3	5	8	11	26

\* Extended with 11.34 kg (25 lbs) ½" (12 mm) gravel per bag.



## COMMERCIAL GRADE FASTSET™ ALL-CRETE™



QUIKRETE FastSet All-Crete is a fast setting non-shrink structural grout for concrete construction and repair.

### Uses:

- Anchor bolts
- Bearing plates
- Floor leveling and repair
- Precast concrete keyways
- Steel column bases
- Roads and bridges
- Filling voids and cracks.

### Features:

- Structural concrete repairs from 1/4" to 24" deep
- Sets in 30 minutes
- Mix to fluid flowable and plastic consistency
- Up to 8000 PSI (55.1 MPa) in 28 days

**Mfr. No. 158553**

**Ship Wt. 22.7 kg bag 30 bags/pallet**

### COVERAGE

No of 22.7 kg (50 lb) bags

Thickness	2 (0.2)	5 (0.5)	10 (0.9)	15 (1.4)	20 (1.8)	50 (4.6)
1" (25mm)	1	1	2	3	4	9
2" (50mm)	1	2	4	5	6	17
*3 (75mm)	1	2	4	6	8	10
4 (100mm)	1	3	5	8	11	26

\* Extended with 11.34 kg (25 lbs) 1/2" (12 mm) gravel per bag.

## MASONRY PRODUCTS

### MASON MIX (TYPE S MORTAR)



Contractor grade, type 'S', pre-blended mortar.

### Used for:

- Brick construction
- Stone construction
- Repairing mortar joints
- Block construction
- Base coat for stucco

### Features:

- Pre-blended, just add water
- High strength
- Exceeds ASTM C270 requirements

**Mfr. No. 113655**

**Ship Wt. 25 kg bag | 56 bags/pallet**

### COVERAGE

1 bag lays 40 bricks

1 bags lays 18 standard blocks (16" x 8" x 8")

1 bags = 22 sq ft of base coat at 1/4" thick

## WATER RESISTANT PARGING MIX



Masonry coating and patching of concrete walls for cosmetic purposes.

### Used for:

- Concrete block
- Concrete & masonry walls
- Base coat for stucco

### Features:

- Easy to apply
- Strong bond
- Resists water penetration
- Can be applied above and below grade

**Mfr. No. 115525**

**Ship Wt. 25 kg bag | 56 bags/pallet**

### COVERAGE

No of 25 kg (55 lb) bags

Square Feet (M <sup>2</sup> )	25 (2.3)	50 (4.7)	300 (27.9)	500 (46.5)	1000 (92.9)
----------------------------------	-------------	-------------	---------------	---------------	----------------

1/8" thick (3 mm)	1	2	8	13	25
----------------------	---	---	---	----	----

1/4" thick (6mm)	3	4	15	25	50
---------------------	---	---	----	----	----

All yields are approximate and do not allow for waste or uneven sub-grade, etc.

## QUIKWALL SURFACE BONDING CEMENT - GRAY



QUIKWALL Surface Bonding Cement is a premium resurfacing product.

It eliminates the need for mortar in block wall construction.

### Used for:

- Surface bonding and resurfacing of concrete and masonry walls

### Features:

- Strengthens and waterproofs block walls without mortar
- Superior bond
- Interior and exterior use

**Mfr. No. 123151**

**Ship Wt. 22.7 kg bag | 35 bags/pallet**

### COVERAGE

No of 22.7 kg (50 lb) bags

Square Ft (M <sup>2</sup> )	25 (2.3)	50 (4.7)	300 (27.9)	500 (46.5)	1000 (92.9)
--------------------------------	-------------	-------------	---------------	---------------	----------------

1/8" thick (3 mm)	1	1	6	10	20
----------------------	---	---	---	----	----

1/4" thick (6 mm)	1	2	12	20	40
----------------------	---	---	----	----	----

All yields are approximate and do not allow for waste or uneven sub-grade, etc.

# CEMENTS AND LIME

## GENERAL USE CEMENT



Normal Portland Cement is a basic ingredient for general purpose concrete

### Used for:

- General purpose concrete

### Features:

- Just add: fine aggregate, coarse aggregate and clean water
- Easy to transport to remote area

Mfr. No.	112425	405942
Ship Wt.	40 kg bag 40 bags/pallet	20 kg bag 72 bags/pallet

### Mix Proportions for Concrete Mix:

CONCRETE STRENGTH	CEMENT	WATER (1)	FINE AGGREGATE (2) (DAMP)	COARSE AGGREGATE (3)	VOLUME
20 MPa	1 bag 40 kg	24 L	140 kg	125 kg	0.14m3 (5 cu. Ft)
25 MPa	1 bag 40 kg	22 L	115 kg	120 kg	0.13m3 (4.5 cu. Ft)
30 MPa	1 bag 40 kg	20 L	105 kg	110 kg	0.12m3 (4.2 cu. Ft)
32 MPa (with air entrainment) **	1 bag 40 kg	18 L	95 kg	100 kg	0.11m3 (3.8 cu. Ft)

## MCS (MORTAR S) CEMENT



Mortar S Cement, is a type 'S' cement.

### Used for:

- Making: Stucco-finish, Base Coat, Mortars, Parging and other masonry applications.

### Features:

- Mortar S Cement only requires the addition of sand and water for masonry applications

Mfr. No. 112525

Ship Wt. 34 kg bag | 40 bags/pallet

### COVERAGE

Mix 1 - 34 kg bag mortar cement with 2 ¼ to 3 parts loose, damp sand for mortar applications



---

## HE (TYPE 30) PORTLAND CEMENT



Type HE is a High Early Strength Portland Cement.

### Used for:

- Applications where high early strengths are required

**Mfr. No.** 112479

**Ship Wt.** 40 kg bag | 40 bags/pallet

---

## HS (TYPE 50) PORTLAND CEMENT



LAFARGE Type HS Portland Cement

### Used for:

- Applications that require high levels of sulphate resistance.

**Mfr. No.** 9994022, 9994005

**Ship Wt.** 20 kg bag | 72 bags/pallet  
40 kg bag | 40 bags/pallet

---

## WHITE PORTLAND CEMENT | FEDERAL WHITE



White Portland Cement Type I is a true Portland cement

### Used for:

- White or colouring applications.
- Federal White Cement can be used for all types of architectural or structural concrete construction where a whiter or brighter color may be needed for aesthetic or safety reasons.
- Federal White Cement may also be used to satisfy low alkali requirements.

**Mfr. No.** 9994010

**Ship Wt.** 40 kg bag | 40 bags/pallet

## PORTLAND CEMENT LIME BLEND



TARGET Portland Cement Lime Blend is used for making mortars - ensuring uniformity during construction. It is prepared under tight quality control standards to ensure consistency.

### Used for:

- TARGET Portland Cement Lime Blend yields high strength mortar

### Features:

- TARGET Portland Cement lime mortars exhibit superior bond characteristics, less shrinkage and cracking than other mortars resulting in greater resistance to water penetration.

**Mfr. No. 405951**

**Ship Wt. 30 kg bag | 50 bags/pallet**

## HYDRATED LIME – TYPE 'S'



### Used for:

- Mixing with cement and sand to make mortar, stucco and other masonry products
- Agricultural use

### Features:

- Fine Grade

**Mfr. No. 9994028**

**Ship Wt. 23 kg bag | 50 bags/pallet**

## HYDRATED LIME – TYPE 'N'



### Used for:

- Mixing with cement and sand to make mortar, stucco and other masonry products
- Agricultural use

### Features:

- Fine Grade

**Mfr. No. 9994035**

**Ship Wt. 22.68 kg bag | 50 bags/pallet**

## REPAIR PRODUCTS - BAGS

### BONDED TOPPING MIX



Concrete repair material designed for thin overlays and repair of concrete up to 1/2".

#### Used for:

- Overlays
- Levelling
- Damaged and cracked concrete

#### Features:

- High strength
- Strong bond
- 90 minute set
- Foot traffic in 2.5 hours
- Trowels to a featheredge

#### COVERAGE

1 – 18 kg bag = 18 ft sq at 1/4" thickness

**Bag Mfr. No. 113318**

**Ship Wt. 18 kg bag | 56 bags/pallet**

### RECAP™ RESURFACER



A special blend of portland cement, sand, polymer modifiers and other additives. Designed to provide a shrinkage compensated repair material for making thin repairs to sound concrete in need of surface renewal. Can be squeegee, trowel or brush applied.

#### Used for:

- Sidewalks
- Concrete Floors
- Patios
- Floors
- Pool Decks
- Driveways
- Parking Decks
- Curbs

**Mfr. No. 113148**

**Ship Weight 18 kg bags 56 bags / pallet**

#### COVERAGE \*

##### Squeegee Application

Square Feet (m <sup>2</sup> )	35 (3.3)	90 (8.4)	200 (18.6)	300 (27.9)	500 (46.5)
1/16" (1.5mm) thick # of bags	1	2	3	4	7

##### Thicker Application

1/8" (3mm) thick # of bags	1	3	6	9	14
1/4" (6mm) thick # of bags	2	5	11	17	27
3/8" (9mm) thick # of bags	3	7	15	23	39

\* All yields are approximate and do not allow for waste or uneven sub-grade, etc.



## FAST-SET SELF-LEVELING FLOOR RESURFACER



### COVERAGE

1 – 22.7 kg bag = 14 L (0.50 cu)  
At 6.4 mm (1/4") thick each bag will cover  
approx. 2.3 m<sup>2</sup> (25 ft<sup>2</sup>) of flat surface

QUIKRETE New & Improved Fast-Setting Self-Leveling Floor Resurfacer is a self-finishing floor topping and underlayment specially formulated to work without troweling.

### Used for:

- Precast concrete plank
- New concrete floor slabs with unacceptable finishes
- Existing concrete floors with damaged finishes
- Over wood floor systems, utilizing expanded metal lath reinforcement
- May be used for outdoor service

### Features:

- Can be used as a wear surface for light industrial floors.
- Works without troweling.

**Mfr. No.** 124958

**Ship Wt.** 22.7 kg bag | 35 bags/pallet

## BLACK TOP PATCH



### COVERAGE

1 bag covers 2 sq ft at 2" thickness

Blacktop Patch is an asphalt cold patch for repairing pot holes and large cracks over 25 mm (1 inch).

### Used for:

- Asphalt pavements such as driveways
- Parking lots
- Roads
- Playground and pathways

### Features:

- Ready to use
- No mixing or heating required
- Traffic can begin immediately after levelling and compacting

**Mfr. No.** 170125

**Ship Wt.** 25 kg bag | 30 bags/pallet

## SANDS AND AGGREGATE PRODUCTS

### PREMIUM PLAY SAND



A versatile sand.

#### Used for:

- Children's sandbox
- Traction for snowy and icy surfaces
- Base and between joints for concrete pavers
- Lawn and garden conditioner

#### Features:

- Heat sterilized
- Washed and screened
- Free of most dust

**Mfr. No. 111325**

**Ship Wt. 25 kg bag | 48 bags/pallet**

#### COVERAGE

1 bag = ½ cubic ft (12" x 12" x 6" thick)

### ALL PURPOSE GRAVEL



Multi use gravel for decorative and landscaping applications.

#### Used for:

- Landscaping
- Drainage
- Window wells
- Fish ponds
- Concrete

#### Features:

- Easy to pour
- Easy to store
- Easy to transport
- Durable plastic bag

**Mfr. No. 115125**

**Ship Wt. 25 kg bag | 30 bags/pallet**

#### COVERAGE

1 bag = ½ cubic ft

## BASE ROCK



### COVERAGE

1 bag = ½ cubic ft

A levelling base for masonry products and other applications.

#### Used as a base for:

- Pavers
- Flagstone
- Brick
- Retaining walls
- Walkways and Driveways

#### Features:

- Saves time
- Professional quality
- Easy to use
- Durable plastic bag

**Mfr. No. 115155**

**Ship Wt. 25 kg bag | 30 bags/pallet**

## PATIO PAVER JOINTING SAND



### COVERAGE

36 kg (80 lb) bag = 7 to 9 m<sup>2</sup> (75 to 100 ft<sup>2</sup>)

Properly graded fine sand for filling joints between pavers, flagstone and other masonry products.

#### Used for:

- Patios
- Sidewalks
- Driveways

#### Features:

- Washed and dried
- Properly screened
- Angular for stability
- Durable plastic bag

**Mfr. No. 115036**

**Ship Wt. 36 kg bag | 42 bags/pallet**

## TRACTION SAND



Ideal for traction on all surfaces in icy conditions.

#### Used for:

- Icy and snowy surfaces
- Added vehicle weight

#### Features:

- Re-usable poly bag
- Angular
- Easy to pour

**Mfr. No. 115831**

**Ship Wt. 18 kg bag | 48 bags/pallet**



## SILICA ABRASIVE 30-50, 16-30, 12-40, 12-50, 20-40



TARGET® Silica Abrasives are high quality, close graded silica sands which undergo up to three washings to provide a clean, high quality material.

### Uses:

- Target Silica Abrasives are suitable for sandblasting of steel, concrete or wood in preparation for coating or repair, to obtain architectural effects in concrete or wood, an aggregate for cementitious or polymer grouts, mortars and concrete and for foundry mold sand and traction sand.

**Mfr. No. 99933050, 99931630, 99931240, 99931212, 99932040**

**Ship Wt. 22.7 kg bag | 72 bags/pallet**

## 1/4 DOWN – LIMESTONE



1/4" Down-Limestone provides a firm, stable, foundations for interlocking pavers, flagstone, bricks, patio block, concrete slabs and anchoring of posts.

### Used for:

- Paver base
- Walkway base
- Concrete slab base
- Setting Posts

### Features:

- Great compaction
- Easy to store
- Easy to transport
- Durable plastic bag
- Only available from Winnipeg Plant

**Mfr. No. 116036**

**Ship Wt. 25 kg bag | 30 bags/pallet**

### COVERAGE

1 bag = 1/2 cubic ft

## EARTH ESSENTIALS - SAND



### PLAY SAND

Mfr. No. 137550

Ship Wt. 18 kg bag | 70 bags/pallet



### POLYMERIC JOINTING SAND

Mfr. No. 137556

Ship Wt. 18 kg bag | 70 bags/pallet

## EARTH ESSENTIALS - STONES, PEBBLES & ROCKS



### LIMESTONE SCREENINGS

Mfr. No. 137546

Ship Wt. 18 kg bag | 70 bags/pallet



### BEACH PEBBLES

Mfr. No. 137517

Ship Wt. 18 kg bag | 70 bags/pallet



### RED CRUSHED TILE

Mfr. No. 137530

Ship Wt. 18 kg bag | 70 bags/pallet



### PEA GRAVEL

Mfr. No. 137510

Ship Wt. 18 kg bag | 70 bags/pallet



### WHITE ROCK

Mfr. No. 137504

Ship Wt. 18 kg bag | 70 bags/pallet



### DRAINAGE GRAVEL

Mfr. No. 137520

Ship Wt. 18 kg bag | 70 bags/pallet

## MISCELLANEOUS PRODUCTS

### QUIK-TUBE® BUILDING FORMS




The QUIK-TUBE® Building Forms are ridged fibre building form tubes that eliminate the need to build wood forms.

#### Used for:

- Mailbox bases
- Deck supports
- Columns

Dia. x Length	6" x 8'	8" x 8'	10" x 8'	12" x 8'
Mfr. No.	692316	692251	692252	692253
Min Order	3	4	4	4

### WALK MAKER® BUILDING FORM



692132 • Country Stone Pattern

Reusable plastic moulds. Fill the mould with concrete mix (approx 1 ½ bags of 25 kg concrete mix fills 1 mould), trowel, and remove the mould. For best results use QUIKRETE® 6000.

#### Used for:

- Walkways
- Garden Paths
- Patios
- Courtyards

#### Features:

- Customize the color with QUIKRETE® Liquid Cement Colors

#### COVERAGE

Approx. 1 ½ bags of 25 kg QUIKRETE 6000 concrete mix to one mould.

**Mfr. No. 692132 – Country Stone Pattern**

**Available: 1 pc 2' x 2' x 2" | 6 per case**



## LIQUID CEMENT COLOUR



### COVERAGE

Will colour up to 2 – 25 kg (55 lb) bag of Concrete, Mortar, or Sand Mix

More intense colour can be achieved by using additional Cement Colour. Do not use more than one bottle per 25 kg (55lb)

A liquid coloring agent used to customize the color of your concrete project.

Add correct amount of dry concrete mix or mortars to water for a proper consistency. One bottle will mix with two 25kg (55lb) bags of Concrete Mix. Available in Red, Brown, Buff, Charcoal.

### Used for:

- Adding color to Walk Maker™ projects
- Adding color to any concrete, mortar, sand topping or stucco project
- Permanent integral color

### Features:

- Add colour to a variety of projects including: curbs, driveways, fishponds, and stucco
- Available in 4 colours

Mfr. No.	131720	131721	131722	131723
Colour	Charcoal	Brown	Buff	Red
Ship Wt. 296 ml - 12 bottles/case				

## BACKER ROD



A foam rope used to partially fill large cracks, gaps and joints before applying sealant. Use for horizontal and vertical applications.

### Used for:

- Expansion joints
- Curtain wall joints
- Partitions
- Log construction
- Pavement joints
- Pre-cast units

### Features:

- Backer Rod can be used as a temporary seal, or inserted into a joint to control sealant depth
- To create a backstop
- Allows for tooling of sealant
- Allows for proper wetting of the joint surfaces for sealing

**Mfr. No. 691741**

**1 piece 3/4" dia. X 20' | 12 per case**

## EXPANSION JOINT STRIPS



Made from resilient wood fibers to prevent damage during expansion and contraction of concrete. Weather resistant.

### Used for:

- Driveways, sidewalks and patios
- Between concrete slabs and to separate slabs from structures

**Mfr. No. 691706**

**Available in: 5' long strips | 40 strips per carton**

## ACRYLIC FORTIFIER



An acrylic resin admixture designed to enhance bonding and water resistance of concrete patching materials, stucco, surface bonding cement, thin-set mortars and tile grouts. Exceeds the requirements of ASTM C 1438

### Used for:

- Improves bonding to existing surfaces
- Eliminates moist curing in most circumstances
- Reduces permeability

### Features:

- Increases bond
- Strengthens concrete
- Helps protect concrete from environment

**Mfr. No. 861016**

**Ship Wt. 0.95L bottle - 6 per case**

### MIXING

Shake well before using.

Use the recommended amount of Concrete Acrylic Fortifier along with sufficient water to provide proper consistency

For QUIKRETE® Quick-Setting Cement & QUIKWALL® Surface Bonding Cement, add 1.9 L of Concrete Acrylic Fortifier per 22.7 kg bag

## CONCRETE & ASPHALT CLEANER - CONCENTRATE



A multi-purpose cleaner that is safe to use on any hard surface where water can be used. Use prior to any repair project to achieve the strongest bond. Non-toxic, non-flammable and contains no acid.

### Used for:

Removing soil grease, oil, etc. from all types of masonry, concrete, mortar and grout

### Cleans:

- Brick
- Slate
- Flagstone
- Quarry tile
- Driveways
- Grout in ceramic tile
- Parking lots
- Garage floors
- Gas stations
- Industrial plant floors
- Tools and Lawnmowers

### APPLICATION

Light soil: One part to 6 parts fresh water.

Medium soil: One part to 4 parts fresh water

Heavy soil: Dilute 1:1 or use full strength.

**Mfr. No. 860112**

**Ship Wt. 946 ml | 6 per case**

## ACRYLIC CONCRETE CURE & SEAL (SATIN)



Concrete sealer is used for curing, protecting and sealing concrete surfaces.

### Used for:

- Curing new concrete
- Protects concrete against water, salt, oils etc.
- Protects concrete against graffiti on concrete walls
- Protects concrete from environment

### Features:

- Attractive satin look
- Makes surface easier to clean
- Can be sprayed, broomed or roller applied

**Mfr. No. 873102**

**Ship Wt. 3.8 L | 4 pails/case**

### COVERAGE

1 x 3.8 L = 14-18 m<sup>2</sup> (150-200 ft<sup>2</sup>).

## REPAIR PRODUCTS – PATCHING PRODUCTS

### BONDED TOPPING MIX



#### COVERAGE

1-4.5 kg pail = 3¼ ft sq at ¼" thickness

Concrete repair material designed for thin overlays and repair of concrete up to 1/2".

#### Used for:

- Overlays
- Levelling
- Damaged and cracked concrete

#### Features:

- High strength
- Strong bond
- 90 minute set.
- Foot traffic in 2.5 hours
- Trowels to a featheredge

**Mfr. No. 113304**

**Ship Wt. 4.5 kg pail | 4 pails/case**

### HYDRAULIC WATER STOP CEMENT



#### COVERAGE

1 x 4.5 kg pail will fill a crack ½" W x 1 ½" D x 15' L

Rapid setting, high strength repair material designed to plug active water leaks instantly in concrete and masonry.

#### Used for:

- Basement walls
- Retaining walls
- Swimming pools
- Instant anchoring
- Foundation walls

#### Features:

- High strength (2000 psi (13.8 MPa) in 30 minutes)
- 3-5 minute set

**Mfr. No. 112612**  
**Ship Wt. 4.5 kg pail**  
**4 pails/case**

**112606**  
**9 kg pail**



## ANCHORING CEMENT



### COVERAGE

Each 4.5 kg pail will yield approximately 0.08 cu ft (2.4 L)

Rapid setting grout.

#### Used for:

- Anchoring of posts, rails and bolts in concrete
- Filling of cracks and voids
- Patching concrete

#### Features:

- High strength (2000 psi (13.8 MPa) in 2 hours, 7000 psi (48.3 MPa) at 28 days)
- Fast setting (10-30 minutes)
- Flowable

**Mfr. No. 124512**

**Ship Wt. 4.5 kg pail | 4 pails/case**

## QUICK-SETTING CEMENT



For concrete repairs where rapid setting is required.

#### Used for:

- Steps
- Curbs
- Walls
- Overhead

#### Features:

- Sets fast (10-15 minutes)
- High strength, strong bond
- Can be applied horizontally, vertically and overhead
- Can be molded or sculpted

**Mfr. No. 124012**

**Ship Wt. 4.5 kg pail | 4 pails/case**

## CONCRETE BONDING ADHESIVE



Permanently bonds new concrete to existing concrete.

### Used for:

- Bonding new concrete to old concrete
- Bonding new plaster and stucco to old plaster and stucco

### Features:

- Indoor/Outdoor application
- Apply by brush roller or spray to the thickness of a coat of paint
- Concentrated

Mfr. No.	990203	990216
Ship Wt.	3.8L bottle 4 per case	0.95L bottle 6 per case

### COVERAGE

Paint-on application 14-28 m<sup>2</sup> (150-300 ft<sup>2</sup>) per 3.8 L

Slurry coat application 7 m<sup>2</sup> (75 ft<sup>2</sup>) per 3.8 L

## CONCRETE PATCHING COMPOUND



A ready-to-use concrete repair for making repairs to cracks, holes and breaks (up to 1/4" wide) in concrete, stucco or masonry walls, sidewalks, patios, driveways, etc.

### Used for:

- Repairs and fills spalls (surface imperfections) and cracks up to 1/4" (6 mm) deep in concrete, masonry, stucco, sidewalks, patios, walkways and steps.

### Features:

- No mixing required
- Dries quickly to a durable and flexible finish
- Weather resistant
- Excellent adhesion
- Textured to blend with concrete surfaces
- Easy clean up with water before product dries
- Use for non-structural cosmetic repairs

### COVERAGE

3.25 sq ft (0.3 M<sup>2</sup>) at a 1/8" (3 mm) thickness.

Mfr. No. 865036

Ship weight: 946 ml | 12 per case

## ZIP AND MIX REPAIR MORTAR



### COVERAGE

Each 1.36 kg bag will yield 0.03 cubic feet of material

ZIP AND MIX Repair Mortar is a structural mortar repair.

#### Used for:

- Repairing concrete, masonry and stucco surfaces up to 2 inches in thickness. It can be used on driveways, sidewalks, patios, steps, concrete and masonry walls.

#### Features:

- Just add water to bag, mix and apply
- Use on vertical and horizontal surfaces
- Superior bonding
- 4500 psi (31.3 MPa) in 28 days

**Mfr. No. 124116**

**Ship Wt. 1.36 kg bag | 6 bags per case**

## PRE-MIXED STUCCO PATCH



### COVERAGE

Each 0.95 L (1 qt) pail will cover approx 3.25 sq. ft (0.3 M<sup>2</sup>) at 1/8" (3 mm) thickness.

A ready-to-use acrylic stucco repair.

#### Used for:

- Making repairs to cracks, breaks and holes up to 1/4" (6 mm) thick in stucco surfaces.

#### Features:

- Dries to a durable and flexible finish
- Sanded formula blends with the texture of surrounding stucco

**Mfr. No. 865033**

**Ship Wt. 0.95 L pail | 12 pails / case**

## EXTERIOR STUCCO PATCH



### COVERAGE

4.5 kg pail yields 5 m<sup>2</sup> (6 ft<sup>2</sup>) @ 1/4"

A finish coat stucco.

#### Used for:

- Repairing broken, cracked or damaged stucco.

#### Features:

- White in colour
- Resistant to shrinkage cracks
- Can be textured and colored to match existing stucco
- Paintable

**Mfr. No. 120145**

**Ship Wt. 4.5 kg pail | 4 pails/case**

## REPAIR PRODUCTS – JOINT AND CRACK REPAIR

### GREY CONCRETE CRACK SEALER



A latex formulation designed to adhere to horizontal concrete surfaces.

#### Used for:

- Repairing cracks in concrete
- Sidewalks
- Patios
- Driveways

#### Features:

- Flows well into cracks
- Easy to apply

**Mfr. No. 864002**

**Ship Wt. 946 ml squeeze bottle | 6 per case**

#### COVERAGE

946 ml fills approximately: 18 m (60 ft)  
of crack at 1/4" x 1/4"

### CONCRETE REPAIR



A superior sanded acrylic latex formulation for crack repair in concrete, including concrete, stucco or masonry walls, sidewalks, patios and driveways.

#### Used for:

- Repairing and filling cracks up to 12 mm (1/2") in concrete, masonry, stucco, sidewalks, patios and driveways
- Vertical or horizontal surfaces

#### Features:

- Dries quickly to a tough and flexible finish
- Helps prevent water and ice damage to concrete surfaces
- Weather resistant
- Excellent adhesion
- Textured to blend with concrete surfaces
- Easy clean up with water before product dries

**Mfr. No. 862012**

**Ship Wt: 296 ml | 12 tubes/case**

#### COVERAGE

296 ml tubes will yield about 7.3 m at a 6 mm (1/4")  
diameter bead or 3.7 m (12 lineal feet) for a 9 mm  
(3/8") diameter bead



## STUCCO CRACK REPAIR



Stucco Crack Repair is an easy to use crack repair for stucco.

### Used for:

- Filling and sealing cracks in stucco up to 12 mm (1/2")

### Features:

- Blends with texture of surrounding stucco
- Paint after 24 hours
- Works on horizontal and vertical surfaces
- Excellent adhesion

**Mfr. No. 865011**

**Ship Wt. 296 ml | 6 tubes / case**

### COVERAGE

Each 296 ml tube will yield 3.7 m (12 linear feet) at 6 mm (1/4") bead.

## MORTAR REPAIR



Acrylic repair for mortar joints.

### Used for:

- Re-pointing and repairing mortar joints
- Concrete crack repair

### Features:

- Square applicator tip for easy application
- Flexible
- Strong bond
- Mortar grey
- Fits standard caulking gun

**Mfr. No. 862002**

**Ship Wt. 296 ml | 6 tubes/case**

### COVERAGE

One cartridge fills 10 ft of 3/8" x 3/8" voids

## FIREPLACE MORTAR



A silicate based refractory cement caulk

### Used for:

- Tuck-pointing damaged fireplace mortar joints
- Repairing cracked or chipped firebricks in fireplaces and wood-burning stoves.

### Features:

- Fireplace Mortar provides excellent adhesion and when exposed to fire is strengthened to firebrick hardness.
- Meets ASTM E 136-04
- Fireplace safe to 1093°C (2000°F)
- As strong as fire brick
- Easy clean-up while wet

**Mfr. No. 862025**

**Ship Wt. 296 ml tube | 12 tubes per case**

### COVERAGE

Approximately 100 linear ft. (30.5 m) for a 1/8" (3 mm) diameter bead

## POLYURETHANE MORTAR JOINT SEALANT



Polyurethane Mortar Joint Sealant is a high performance construction grade polyurethane sealant.

### Used for:

- Waterproofing and sealing mortar joints and bonds to most construction materials.

### Features:

- Excellent adhesion
- Non-sag formulation
- Dries to touch in 2 hours
- Flexible

**Mfr. No. 862019**

**Ship Wt. 296 ml | 12 tubes/case**

### COVERAGE

Each 10.1 oz (300 ml) tube can be applied to approximately 12 linear feet (3.7 m) in a 3/8" (10 mm) bead

## POLYURETHANE SEALANT GRAY – SELF LEVELLING



Polyurethane Self-Levelling Sealant is a high performance construction grade polyurethane sealant.

### Used for:

- Sealing cracks and joints in horizontal concrete surfaces. It can be used for concrete floors, driveways, patios, steps, basements, pool decks and more.

### Features:

- Superior adhesion
- Durable and flexible
- Resistant to moisture
- Virtually no shrinkage

**Mfr. No. 866012**

**300 ml tube | 12 tubes / case**

**Mfr. No. 866032**

**858 ml tube | 6 tubes / case**

### COVERAGE

12 linear feet (3.7 m) at ½" x ¼" (12 x 6 mm) joint

## POLYURETHANE SEALANT – NON-SAG



A high performance, construction grade polyurethane sealant designed for vertical and overhead surfaces.

### Used for:

- Vertical or horizontal expansion joints in concrete, stucco or masonry
- Caulking around window and door openings
- Sealing skylights and chimney flashings

### Features:

- The non-sag formula provides superior adhesion and flexibility. Meets ASTM C 920, Type S, Grade NS.

**Mfr. No. 866013**

**Ship Wt. 296 ml tube | 12 tubes / case**

### COVERAGE

12 linear feet (3.7 m) at ½" x ¼" (12 x 6 mm) joint

## FASTSET™ ANCHORING EPOXY



FASTSET™ Anchoring Epoxy is a commercial grade, fast-setting, two component structural epoxy.

### Used for:

- Anchoring such things as bolts, rebar, railings, threaded rod, etc, in concrete, masonry and rock.

### Features:

- Sets fast (in 3-4 minutes)
- High strength
- Non-sag
- For vertical and horizontal applications
- Sets in sub-zero temperatures

**Mfr. No. 862032**

**Ship Wt. 254 ml tube | 6 tubes / case**

### COVERAGE

Each 254 ml tube will yield 3.2 m (0.3 linear feet) at 6 mm (¼") bead.

## COMMERCIAL GRADE POLYURETHANE ADHESIVE



Commercial Grade Adhesive is a high performance, construction grade adhesive.

### Used for:

- Permanently bonding concrete masonry and all types of construction materials such as wood, glass, metal and plastic.

### Features:

- Superior bond
- Water resistant
- Freeze/thaw resistant
- Flexible

**Mfr. No. 990212**

**Ship Wt. 300 ml | 12 per case**

**Mfr. No. 990213**

**Ship Wt. 858 ml | 6 per case**

### COVERAGE

Each 300 ml tube can be applied to approximately 12 linear feet (3.7 m) in a 3/8" (10 mm) bead



## WATERPROOFING PRODUCTS

### XYPEX HIGH 'N DRY



#### COVERAGE

1 lb = 6 square feet

For permanent waterproofing of concrete.

#### Used for:

- Basement walls
- Retaining walls
- Concrete ponds

#### Features:

- Penetrates deep into concrete
- Withstands water pressures
- Easy to apply
- Works under wet conditions
- Can be applied to the inside or outside of basement walls

Mfr. No.	9991058	9991059	9991060
Ship Wt.	11 kg pail	5 kg pail	2.27 kg pail
	1 per case	1 per case	6 per case

### XYPEX PATCH 'N PLUG



#### COVERAGE

1 lb = 6 square feet

A specially designed, fast setting, non-shrink, high-bond-strength, hydraulic cement compound for concrete patching and repair. Patch 'n Plug stops flowing water in seconds and is used to seal cracks, tie holes, and other defects in concrete.

#### Used for:

- Basements walls
- Retaining walls
- Swimming pools
- Instant anchoring
- Foundation walls

#### Features:

- High strength (2000 psi in 30 minutes)
- 3-5 minutes set
- Non metallic. Non toxic

Mfr. No.	9991062	9991063
Ship Wt.	2.27 kg pail	9 kg pail
	6 per case	1 per case



## CONTACT INFORMATION



FOR TECHNICAL SALES & ASSISTANCE | CEMENT & CONCRETE PRODUCTS

---

### CONSUMER SALES MANAGER

**Randy Stone** Tel: 1 604 649 4242 Email: rstone@quikrete.ca

---

### SALES REPRESENTATIVES

<b>Mara Marsden</b>	Tel: 1 604 417 2188	Email: mmarsden@quikrete.ca
<b>Brent Foster</b>	Tel: 1 403 471 0529	Email: bfoster@quikrete.ca
<b>Tammy-Lee Klassen</b>	Tel: 1 403 690 2185	Email: tklassen@quikrete.ca
<b>Mike Coghill</b>	Tel: 1 204 654 8320	Email: mcoghill@quikrete.ca

---

### CORPORATE SALES OFFICE:

8535 Eastlake Drive  
Burnaby, BC  
Canada V5A 4T7

Tel: 1 604 444 3620 Fax: 1 604 420 3616

Toll Free: 1 800 575 7700

---

### PLANT LOCATIONS

#### VANCOUVER PLANT:

1080 Bradner Road  
Abbotsford, BC  
Canada V4X 1H8

Tel: 1 604 856 7976

Toll Free: 1 888 484 1258

Fax: 1 604 856 7972

Orders: AbbotsfordOrder@Quikrete.ca

**Mara Marsden**

Tel: 1 604 417 2188

Email: mmarsden@quikrete.ca

#### CALGARY PLANT:

5150 90 Avenue, SE  
Calgary AB  
Canada T2C 2T2

Tel: 1 403 279 8189

Toll Free: 1 800 661 8482

Fax: 1 403 279 4829

Orders: CalgaryOrder@Quikrete.ca

**Brent Foster**

Tel: 1 403 471 0529

Email: bfoster@quikrete.ca

**Tammy-Lee Klassen**

Tel: 1 403 690 2185

Email: tklassen@quikrete.ca

#### WINNIPEG PLANT:

400 Pandora Avenue W  
Winnipeg MB  
Canada R2C 3A5

Tel: 1 204 654 8320

Toll Free: 1 855 654 8320

Fax: 1 204 654 8329

Orders: WinnipegOrder@Quikrete.ca

**Mike Coghill**

Tel: 1 204 654 8320

Email: mcoghill@quikrete.ca

